

CITY OF JOLIET, ILLINOIS EASTSIDE WASTEWATER TREATMENT PLANT DIGESTER IMPROVEMENTS JULY 2006



GENERAL LOCATION MAP



PROJECT LOCATION MAP

CITY OF JOLIET, ILLINOIS EASTSIDE WWTP DIGESTE IMPROVEMENTS



DESIGN FIRM REGISTRATION No. 184-000450

1817 SOUTH NEIL STREET SUITE 100
CHAMPAIGN. ILLINOIS

DESIGNED BY: RJC/JLE
DRAWN BY: CSH/CWL
CHECKED BY: RLV
DATE CHECKED: 07/06

NOTE: DIMENSIONAL DATA IS

NOT TO BE OBTAINED BY SCALING ANY PORTION OF

THIS DRAWING.


TE REVISION
PROJECT No.

J02570

VER DRAWING

DRAWING No.

DRAWING 1 OF 41



CONSTRUCTION SEQUENCE

<u>DIGESTER AND GAS PIPING SEQUENCING</u>

- 1. CITY TO DRAIN DIGESTER NO. 3 AS LOW AS POSSIBLE WITH EXISTING TRANSFER PUMPS.
- 2. CONTRACTOR IS RESPONSIBLE FOR CLEANING AND REMOVAL OF ANY REMAINING SLUDGE.
- CONTRACTOR TO REMOVE COVER ON DIGESTER NO. 3.
- REMOVE EXISTING GAS PIPING AND ASSOCIATED EQUIPMENT AS SHOWN ON PLANS.
- INSTALL MIXING NOZZLES AND ASSOCIATED PIPING IN DIGESTER.
- INSTALL SLUDGE MIXING PUMPS AND PIPING UP TO ISOLATION VALVES FOR EACH DIGESTER.
- REPLACE GAS PIPING WITHIN DIGESTER.
- INSTALL WASTE GAS BURNER AND ASSOCIATED GAS PIPING, METERS, ETC.
- INSTALL GAS PIPING HEADER IN DIGESTER BUILDING WITH ISOLATION VALVES TO EACH DIGESTER.
- REPLACE AND PAINT COVER.
- 4. PUT DIGESTER NO. 3 BACK INTO SERVICE.
- 5. PERFORM START-UP AND OPERATION OF MIXING PUMPS AND WASTE GAS BURNER.
- 6. CITY TO DRAIN DIGESTER NO. 2 AS LOW AS POSSIBLE WITH EXISTING TRANSFER PUMPS.
- 7. CONTRACTOR IS RESPONSIBLE FOR CLEANING AND REMOVAL OF ANY REMAINING SLUDGE.
- 8. CONTRACTOR TO REMOVE COVER ON DIGESTER NO. 3.
 - REMOVE EXISTING GAS PIPING AND ASSOCIATED EQUIPMENT AS SHOWN ON PLANS.
 - INSTALL MIXING NOZZLES AND ASSOCIATED PIPING IN DIGESTER.
 - REPLACE GAS PIPING WITHIN DIGESTER.
 - INSTALL SUPERNATANT TREE AND ASSOCIATED PIPING, ETC.
 - REPLACE AND PAINT COVER.
- 4. PUT DIGESTER NO. 2 BACK INTO SERVICE.
- 5. CITY TO DRAIN DIGESTER NO. 1 AS LOW AS POSSIBLE WITH EXISTING TRANSFER PUMPS.
- CONTRACTOR IS RESPONSIBLE FOR CLEANING AND REMOVAL OF ANY REMAINING SLUDGE.
- 7. CONTRACTOR TO REMOVE COVER ON DIGESTER NO. 1.
 - REMOVE EXISTING GAS PIPING AND ASSOCIATED EQUIPMENT AS SHOWN ON PLANS.
 - INSTALL MIXING NOZZLES AND ASSOCIATED PIPING IN DIGESTER.
 - REPLACE GAS PIPING WITHIN DIGESTER.
 - REPLACE AND PAINT COVER.
- 8. CITY TO DRAIN DIGESTER NO. 4 AS LOW AS POSSIBLE WITH EXISTING TRANSFER PUMPS.
 - CONTRACTOR IS RESPONSIBLE FOR CLEANING AND REMOVAL OF ANY REMAINING SLUDGE.
 - PAINT COVER ON DIGESTER NO. 4.
 - CLEAN GAS PIPING FROM DIGESTER BUILDING UP TO DIGESTER NO. 4.
 - REPLACE GAS PIPING INSIDE DIGESTER NO. 4
- 9. PUT DIGESTER NO. 4 BACK INTO SERVICE.

OVERALL SITE PLAN

SLUDGE STORAGE TANKS SEQUENCING

NOTE: WORK MUST BE COORDINATED WITH CITY TO COINCIDE WITH SLUDGE HAULERS REMOVING SLUDGE.

- 1. CITY WILL EMPTY ONE TANK AT A TIME AS MUCH AS POSSIBLE WITH EXISTING PUMPS.
- 2. CONTRACTOR IS RESPONSIBLE FOR CLEANING TANK AS NEEDED TO INSTALL PIPING CONNECTIONS.
- 3. INSTALL SUPERNATANT LINES ON 4 TANKS, 1 AT A TIME AND MAKE CONNECTIONS TO PARSHALL FLUME.
- 4. START-UP METER AND VALVE CONTROLS.

<u>SEQUENCING NOTES:</u>

- 1. ONLY ONE PUMP OR BOILER MAY BE REPLACED AT A TIME IN EACH OPERATIONAL AREA. PUMPS MUST BE STARTED AND PUT INTO SERVICE FOR MINIMUM 48 HOURS PRIOR TO ADDITIONAL REPLACEMENT.
- 2. CONCRETE WORK, EXTERIOR PAINTING, AND TUCK POINTING MUST BE COMPLETED IN TEMPERATURES ABOVE 50°.
- 3. ALL WORK TO BE COORDINATED WITH OWNER TO MINIMIZE DISRUPTION TO WWTP OPERATIONS.

INDEX OF DRAWINGS

GENERAL

GENERAL NOTES, DRAWING INDEX AND OVERALL PLANT SITE

A-1 DIGESTER BUILDING ROOF PLAN AND DETAILS

DIGESTER BUILDING ROOF DETAILS HANDRAIL REPLACEMENT PLAN

SITE PLAN

PRIMARY TANK GEAR DRIVES

CONTROL BUILDING PLAN AND SECTION RAS PUMPS AND AS PUMPS DEMOLITION AND PROPOSED PLANS AND SECTIONS

WAS PUMP DEMOLITION AND PROPOSED PLAN AND SECTION

DIGESTER BUILDING DEMOLITION PLANS PR-7 DIGESTER BUILDING PLANS AND SECTIONS

PR-8 DIGESTER GAS SCHEMATIC

DIGESTER NO. 1 PLAN AND SECTION

PR-10

DIGESTER NO. 3 PLAN PR-11 DIGESTER NO. 3 SECTION

DIGESTER SITE PIPING PLAN SOLIDS PROCESSING BUILDING DEMOLITION AND PROPOSED PLANS AND SECTIONS

SLUDGE STORAGE SUPERNATANT PLAN PR-15 DETAILS

ELECTRICAL GENERAL NOTES, SYMBOL LIST, AND SEQUENCE OF CONSTRUCTION

ELECTRICAL SITE PLAN

ENLARGED ELECTRICAL SITE PLAN E-4 PROCESS MOTOR SCHEDULE AND CONTROL DIAGRAMS

EXISTING AND PROPOSED POWER ONE-LINE DIAGRAM PRIMARY TANK ELECTRICAL PLANS E-6

E-7 CONTROL BUILDING ELECTRICAL PLANS CONTROL BUILDING FIRST FLOOR ELECTRICAL PLAN AND MCC-E ELEVATION

BLOWER BUILDING BASEMENT ELECTRICAL PLANS

BLOWER BUILDING FIRST FLOOR ELECTRICAL PLAN VFD SCHEDULE AND MCC-D ELEVATION

AERATION PIPE GALLERY ELECTRICAL PLANS F-12 DIGESTER ENLARGED ELECTRICAL PLAN

DIGESTER BUILDING BASEMENT ELECTRICAL PLAN DIGESTER BUILDING FIRST FLOOR ELECTRICAL PLANS

DIGESTER BUILDING MCC-B ELEVATION AND DETAILS SOLIDS PROCESSING BUILDING BASEMENT ELECTRICAL PLANS

SOLIDS PROCESSING BUILDING FIRST FLOOR ELECTRICAL PLAN AND MCC-A ELEVATION

F-18 SLUDGE STORAGE ELECTRICAL PLANS AND NOTES

ELECTRICAL DETAILS ELECTRICAL DETAILS

GENERAL NOTES

- NOT ALL OF THE GAS, POWER, OR TELEPHONE LINES, WHETHER ABOVE OR BELOW GROUND, HAVE BEEN SHOWN ON THE DRAWINGS. THE CONTRACTOR MUST REALIZE THAT THE ACTUAL LOCATIONS OF THE UTILITIES SHOWN ON THE DRAWINGS MAY BE DIFFERENT FROM THE LOCATIONS INDICATED.
- THE LOCATIONS OF THE EXISTING YARD PIPING, SUCH AS RAW SEWAGE LINES, DRAIN LINES, NON-POTABLE WATER LINES, ETC., AS SHOWN ON THE DRAWINGS, HAS BEEN DETERMINED FROM PLANS FOR THE EXISTING FACILITIES AND ARE GIVEN FOR THE CONVENIENCE OF THE CONTRACTOR. THE CONTRACTOR MUST ASSUME RESPONSIBILITY FOR ALL PIPING AND MUST REALIZE THAT THE ACTUAL LOCATIONS MAY BE DIFFERENT FROM THOSE INDICATED ON THE DRAWINGS.
- 3. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO MAINTAIN IN SERVICE THE WASTEWATER TREATMENT FACILITY, ALL EXISTING PROCESS PIPING, AND ALL EXISTING UTILITIES ENCOUNTERED DURING CONSTRUCTION UNLESS OTHERWISE INDICATED IN THE DRAWINGS. ANY PIPING WHICH CAN BE REMOVED DURING CONSTRUCTION WITHOUT UNDUE INTERRUPTION OF SERVICE MAY BE REMOVED AND REPLACED BY THE CONTRACTOR WITH THE PERMISSION OF THE OWNER.
- BEFORE WORKING WITH OR AROUND EXISTING UTILITIES, THE APPLICABLE UTILITY COMPANY SHALL BE CONTACTED BY THE CONTRACTOR.
- 5. THE CONTRACTOR SHALL PRESERVE AND PROTECT PROPERTY MARKERS, SECTION CORNERS, SURVEY MARKS AND CITY BENCH MARKS, SUCH AS STONES, PIPES, OR OTHER MONUMENTS ENCOUNTERED. IF THE CONTRACTOR MUST RELOCATE THE PROPERTY MARKERS OR MONUMENTS, THEIR LOCATION SHALL BE REFERENCED BY A REGISTERED LAND SURVEYOR AND THE OWNER NOTIFIED BEFORE MOVING. ALL PROPERTY MARKERS AND MONUMENTS RELOCATED DURING CONSTRUCTION SHALL BE RE-ESTABLISHED BY A REGISTERED LAND SURVEYOR AT THE CONTRACTOR'S EXPENSE.
- THE CONTRACTOR SHALL FAMILIARIZE HIMSELF WITH THE AREA AND NO EXTRA COMPENSATION CONNECTED WITH OVERHEAD UTILITIES WILL BE ALLOWED.
- 7. THE CONTRACTOR IS RESPONSIBLE FOR DUST AND MUD CONTROL.
- ROADWAY SURFACING AND BASE MATERIALS, OR ANY OTHER PROPERTY REMOVED OR DAMAGED, SHALL BE REPLACED OR REPAIRED AS PROVIDED FOR IN THE SPECIFICATIONS OR OTHER CONTRACT DOCUMENTS.
- 9. THE CONTRACTOR IS RESPONSIBLE FOR ALL CONSTRUCTION TRAFFIC CONTROL.

- 10. IT IS INTENDED THAT GRADING BE PROVIDED TO ASSURE ADEQUATE DRAINAGE AWAY FROM THE BUILDINGS AND STRUCTURES. ALL GRADING SHALL BE APPROVED BY THE OWNER.
- 11. THE CONTRACTOR IS SOLELY AND COMPLETELY RESPONSIBLE FOR JOB SITE CONDITIONS DURING THE COURSE OF CONSTRUCTION OF THIS PROJECT. INCLUDING EROSION CONTROL AND THE SAFETY OF ALL PERSONS AND PROPERTY: THIS REQUIREMENT SHALL APPLY CONTINUOUSLY AND NOT BE LIMITED TO NORMAL WORKING HOURS, AND THE CONTRACTOR SHALL DEFEND, INDEMNIFY AND HOLD THE OWNER AND THE ENGINEER HARMLESS FROM ALL LIABILITY, REAL, OR ALLEGED, IN CONNECTION WITH THE PERFORMANCE OR WORK ON THE PROJECT EXCEPTING FOR LIABILITY ARISING FROM THE SOLE NEGLIGENCE OF THE OWNER OR THE ENGINEER.
- 12. INFORMATION ON DETAIL DRAWINGS TAKES PRIORITY OVER ALL GENERAL DRAWINGS AND SCHEDULES. CONFLICTS SHALL BE RESOLVED ACCORDINGLY.
- WHEN CONNECTIONS ARE TO BE MADE TO EXISTING PIPING AND STRUCTURES, THE LOCATION AND ELEVATION OF THE EXISTING PIPING SHALL BE FIELD VERIFIED AND NOTIFICATION GIVEN TO THE OWNER IF THE EXISTING PIPING IS FOUND TO BE DIFFERENT THAN THAT SHOWN ON THE DRAWINGS.
- 14. THE COST OF ABIDING BY THE PROVISIONS OF PERMITS ISSUED BY VARIOUS AGENCIES SHALL BE CONSIDERED INCIDENTAL TO THE CONTRACT. ALL ASSOCIATED BONDING REQUIREMENTS AND COSTS ARE INCIDENTAL TO THE CONTRACT.
- 15. THE CONTRACTOR IS RESPONSIBLE FOR OBTAINING PERMITS FROM THE WILL COUNTY HIGHWAY DEPARTMENT (815/727-8476) WHEN OVERWEIGHT LOADS ARE TO BE TRANSPORTED TO AND FROM THE PLANT SITE. THE PERMIT WILL BE NECESSARY FOR LOADS EXCEEDING THE STATE MAXIMUM WEIGHT LIMIT OF 73,280 LBS. AN INDIVIDUAL PERMIT WILL BE REQUIRED FOR EACH OVERWEIGHT LOAD. THE CONTRACTOR MAY APPLY FOR THE PERMIT BY PHONE AND PICK UP AND SIGN THE PERMIT AT THE HIGHWAY DEPARTMENT OFFICES IN JOLIET. THE FOLLOWING INFORMATION WILL BE NEEDED:
 - A DESCRIPTION OF THE LOAD.
 - THE LOAD ORIGINATION AND DESTINATION.
 - THE LOAD'S TOTAL LENGTH, WIDTH, AND HEIGHT. WEIGHTS OF SEPARATE COMPONENTS OF THE LOAD (TRACTOR WEIGHT, TRAILER WEIGHT, AND THE WEIGHT OF THE OBJECT
 - BEING MOVED). LICENSE NUMBERS OF THE TRACTOR AND TRAILER BEING USED. DATE THAT THE MOVE WILL TAKE PLACE.

BENCHMARK

TBM #1: NORTHWEST BOLT ON FIRE HYDRANT WEST SIDE OF MCKINLEY NORTH OF MAIN ENTRANCE. ELEV. 523.41

___RJC/JLE DESIGNED BY: DRAWN BY: CSH/CWL CHECKED BY: RLV DATE CHECKED: ____07/06__ NOTE: DIMENSIONAL DATA IS NOT TO BE OBTAINED BY SCALING ANY PORTION OF

ENGINEERS

DESIGN FIRM REGISTRATION

No. 184-000450

1817 SOUTH NEIL STREET

SUITE 100

CHAMPAIGN, ILLINOIS

(217) 373-8900

(217) 373-8923

REVISION

THIS DRAWING.

PROJECT No. J02570

DRAWING TITLE


ES, AND SITE NDEX NDEX LANT G L

DRAWING No.

 \Box

DRAWING 2 OF 41

Mon, 07 Aug 2006 — 3:41pm Last Edited By: CWL Drawing Name: P:\J02570\Joliet Eastside Sludge\Gen—01,02 Cover & General.dwg





DESIGN FIRM REGISTRATION 1817 SOUTH NEIL STREET


CHAMPAIGN, ILLINOIS


_____CWL DATE CHECKED: ____06/06

NOTE: DIMENSIONAL DATA IS NOT TO BE OBTAINED BY SCALING ANY PORTION OF












1817 SOUTH NEIL STREET CHAMPAIGN, ILLINOIS

NOTE: DIMENSIONAL DATA IS NOT TO BE OBTAINED BY SCALING ANY PORTION OF







ENGINEERS
DESIGN FIRM REGISTRATION No. 184-000450

1817 SOUTH NEIL STREET SUITE 100 CHAMPAIGN, ILLINOIS (217) 373-8900 (217) 373-8923


DESIGNED BY: RJC/JLE
DRAWN BY: CSH
CHECKED BY: RLV
DATE CHECKED: 07/06


SCALING ANY PORTION OF


J02570


DRAWING TITLE


DRAWING 10 OF 41


























GENERAL NOTES

- ALL WORK SHALL CONFORM TO THE REQUIREMENTS OF THE 2005 NATIONAL ELECTRICAL CODE THE MOST CURRENT EDITION OF THE NATIONAL ELECTRICAL SAFETY CODE, AND ALL APPLICABLE LOCAL ORDINANCES
- CONTRACTOR SHALL FURNISH ALL MATERIALS FOR A COMPLETE AND WORKABLE SYSTEM.
- CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL REQUIRED PERMITS AND FOR PROVIDING ALL SUPERVISION, LABOR AND TOOLS FOR THE PROJECT.
- ALL WORK IS TO CONFORM TO A TIME SCHEDULE TO BE ESTABLISHED BY THE OWNER.
- CONTRACTOR SHALL COORDINATE THE WORK SCHEDULE WITH THE OWNER AND OBTAIN THE OWNER'S APPROVAL BEFORE ANY WORK INVOLVING A SHUTDOWN IS DONE
- ALL MATERIALS FURNISHED BY THE CONTRACTOR ARE TO BE NEW AND APPROVED BY THE OWNER AS TO MANUFACTURER AND TYPE.
- ALL CONDUITS SHALL BE PROVIDED WITH AN EQUIPMENT GROUNDING CONDUCTOR SIZED IN ACCORDANCE WITH THE 2005 NATIONAL ELECTRICAL CODE.
- ALL LOCATIONS AND DIMENSIONS SHOWN ARE APPROXIMATE. CONTRACTOR SHALL FIELD VERIFY ALL ELECTRICAL EQUIPMENT LOCATIONS AND EQUIPMENT DIMENSIONS

RACEWAY NOTES

- POWER, INSTRUMENTATION AND CONTROL WIRING SHALL BE INSTALLED IN SEPARATE CONDUITS SHIELDED CONDUCTORS SHALL NOT BE INSTALLED IN THE SAME CONDUIT AS ANY UNSHIELDED CONDUCTORS.
- REMOVE ALL UNUSED CONDUIT AND WIRE BACK TO SOURCE ASSOCIATED WITH EQUIPMENT BEING REMOVED OR RELOCATED. CONCEALED CONDUIT BELOW FLOOR OR UNDERGROUND MAY REMAIN IN PLACE.
- ALL CONDUIT FOR POWER, LIGHTING, CONTROL AND INSTRUMENTATION SHALL BE HOT-DIPPED GALVANIZED HEAVY WALL RIGID STEEL. MINIMUM CONDUIT SIZE SHALL BE 3/4".
- ALL UNDERGROUND CONDUITS SHALL BE RIGID STEEL HOT-DIPPED GALVANIZED 1" MINIMUM AND SHALL BE ENCASED IN RED CONCRETE 2'-6" MINIMUM BELOW GRADE, UNLESS OTHERWISE NOTED.
- CONDUIT RUNS SHALL BE ROUTED TO AVOID, AND NEVER RUN BELOW, STEAM, WATER OR OTHER PIPE WHICH MAY HAVE AN ADVERSE EFFECT DUE TO HEAT OR LEAKS. WHERE CONDUIT PARALLELS OR CROSSES SUCH PIPES, A MINIMUM SEPARATION OF 12 INCHES SHALL BE MAINTAINED.
- LIQUID-TIGHT FLEXIBLE CONDUIT (MAXIMUM OF 24") SHALL BE USED IN CONNECTING MOTORS. SENSING ELEMENTS. INSTRUMENTS. SOLENOID VALVES. OR ANY OTHER DEVICE WHICH TRANSMIT VIBRATION OR NOISE, REQUIRE MOVEMENT FOR ADJUSTMENT, OR REQUIRE REMOVAL FOR MAINTENANCE. MINIMUM SIZE OF FLEXIBLE CONDUIT SHALL BE 1/2".
- JUNCTION BOXES, CABINETS, SWITCHES AND OTHER ELECTRICAL EQUIPMENT SHALL BE SOLIDLY ATTACHED PRIOR TO INSTALLATION OF CONDUIT
- CONDUIT. PULL BOXES. CABINETS. ETC. SHALL FORM A CONTINUOUS CONDUCTIVE GROUND SYSTEM. AT TRANSITIONS AND BREAKS, CONDUIT SHALL BE BONDED.
- CONDUIT SHALL NOT BE FASTENED TO OTHER EQUIPMENT OR SO INSTALLED AS TO PREVENT THE READY REMOVAL OF OTHER EQUIPMENT FOR REPAIRS. INSTALLATION OF CONDUITS MUST NOT INTERFERE WITH ACCESS WAYS OR LADDERS.
- 10. ALL NEW CONDUITS INSIDE BUILDINGS SHALL BE PAINTED TO MATCH THE COLOR OF THE WALLS OR THE COLOR OF THE EXISTING CONDUITS.
- 11. ONLY PULLBOXES SPECIFICALLY REQUIRED BY THE ENGINEER IN LOCATIONS SHOWN ARE IDENTIFIED. CONTRACTOR SHALL PROVIDE ALL PULLBOXES REQUIRED TO MEET APPLICABLE
- 12. CONDUITS ENTERING EXTERIOR ENCLOSURES SHALL BE TERMINATED WITH STEEL OR IRON FITTINGS AND T&B EFCOR HUB CONNECTORS.

GROUNDING NOTES

- ALL GROUND CONDUCTORS SHALL BE STRANDED BARE COPPER UNLESS OTHERWISE NOTED AND SIZED AS SHOWN ON THE DRAWINGS.
- BURIED GROUND LOOP SHALL BE BARE COPPER AS INDICATED ON THE DRAWINGS. GROUND LOOP SHALL BE INSTALLED A MINIMUM OF 24" BELOW GROUND SURFACE.
- GROUND RODS SHALL BE 3/4" DIA x 10'-0" LONG COPPER CLAD. CONNECTIONS TO GROUNDING CONDUCTOR SHALL BE WITH EXOTHERMIC WELDS.

WIRING NOTES

- WIRING SHALL BE IDENTIFIED BY PERMANENT WIRE MARKERS AT EACH TERMINATION AND SHALL CORRESPOND WITH THE IDENTIFICATION NUMBERS ON THE DRAWINGS.
- CONDUCTORS SHALL BE CONTINUOUS FROM POINT OF ORIGIN TO THE TERMINATION. NO CABLE SHALL BE SPLICED EXCEPT AS SHOWN ON THE DRAWINGS OR ON EXPLICIT INSTRUCTIONS OF THE OWNER.
- TERMINALS ON THE TERMINAL BLOCK SHALL BE PLAINLY AND PERMANENTLY MARKED TO CORRESPOND WITH THE IDENTIFICATION NUMBERS ON THE DIAGRAMS.
- 4. ALL CABLE AND WIRE SHALL BE STRANDED COPPER. ALUMINUM CABLE AND WIRE ARE NOT ACCEPTABLE. ALL POWER AND CONTROL CABLE SHALL BE CROSS-LINKED POLYETHYLENE (XLP) OR POLYVINYL CHLORIDE (PVC) INSULATION (XHHW OR THHN-THWN), RATED 90°C FOR 600 VOI T.
- CONTRACTOR SHALL FURNISH ALL LIGHTING FIXTURES, CONDUIT, JUNCTION BOXES, AND PULLBOXES AS REQUIRED. ALL OUTDOOR LIGHTING JUNCTION BOXES AND PULLBOXES SHALL BE STAINLESS STEEL NEMA 4X ENCLOSURES.

ELECTRICAL GENERAL NOTES (CONT.)

CONTROL NOTES

- CONTRACTOR SHALL PROVIDE AND INSTALL ALL CABLES AND WIRE FROM CONTROL/INSTRUMENTATION DEVICES BACK TO ASSOCIATED CONTROL PANELS.
- CONTRACTOR SHALL PROVIDE 20% SPARE CONTROL WIRES (MINIMUM OF 3 SPARES) FOR EACH CONTROL DEVICE. CAP SPARE WIRES AND LABEL AS SPARE.

BOX NOTES

- FABRICATED BOXES 24 x 24 INCHES OR SMALLER SHALL BE MADE FROM 10 GAUGE STEEL
- FABRICATED BOXES LARGER THAN 24 x 24 INCHES SHALL BE MADE FROM 1/8" STEEL SHEET.
- BOXES INSTALLED IN AN AREA DEFINED TO BE ACID OR CAUSTIC SHALL BE MADE FROM TYPE 316 STAINLESS STEEL UNLESS INDICATED OTHERWISE ON THE DRAWINGS.
- IN DRY AND/OR CLEAN AREAS CONDUIT ATTACHMENT TO THE BOX SHALL BE MADE BY THE USE OF DOUBLE STEEL LOCK NUT (ONE OF WHICH SHALL BE OF THE BONDING TYPE) AND AN INSULATING BUSHING ON THE END OF EACH CONDUIT TERMINATION IN THE BOX
- IN WET AND/OR DUSTY AREAS AND OUTDOORS, CONDUIT ATTACHMENT TO BOXES SHALL BE MADE WITH A WATERTIGHT CONDUIT HUB AS MANUFACTURED BY EFCOR CO. OR OWNER APPROVED EQUAL
- CONTRACTOR SHALL LEAVE SLACK IN ALL CABLE IN ALL BOXES.
- CONTRACTOR SHALL FURNISH AND INSTALL BARRIERS IN BOXES AS CALLED FOR ON THE DRAWINGS. BARRIERS SHALL BE MADE FROM A MINIMUM OF 10 GAUGE STEEL SHEET AND HELD IN PLACE WITH CLIP ANGLES.
- ALL BARRIERS SHALL BE INSTALLED UPON COMPLETION OF THE INSTALLATION OF CABLE AND SHALL BE REMOVABLE TO PERMIT FUTURE CABLE INSTALLATION
- ALL CABLES WITHIN THE BOX SHALL BEAR A CABLE IDENTIFICATION TAG IN ACCORDANCE WITH THE OWNERS ELECTRICAL SPECIFICATION.

SUGGESTED SEQUENCE OF CONSTRUCTION

THE FOLLOWING IS A SUGGESTED SEQUENCE OF CONSTRUCTION FOR THE UPGRADE TO THE ELECTRICAL DISTRIBUTION SYSTEM FOR THIS PROJECT. IT IS PROVIDED AS A GUIDELINE ONLY. THE CONTRACTOR SHALL SUBMIT THEIR PROPOSED DETAILED SEQUENCE OF CONSTRUCTION AND GET APPROVAL FROM THE OWNER AND ENGINEER PRIOR TO BEGINNING CONSTRUCTION. THIS SEQUENCE OF CONSTRUCTION SHALL CORRELATE WITH THE MILESTONES AND ACTIVITY DESCRIPTIONS IN THE CONSTRUCTION SCHEDULE.

A.EXCEPT AS SPECIFICALLY NOTED HEREIN, MAINTAIN EXISTING ELECTRICAL DISTRIBUTION SYSTEM AT ALL TIMES.

- B.ALL POWER OUTAGES AT THE PLANT MUST BE COMPLETED DURING LOW FLOW AT THE PLANT (THERE SHALL BE 3 DAYS OF NO RAINFALL PRIOR TO THE OUTAGE AND NO FORCASTED RAINFALL DURING THE OUTAGE). POWER OUTAGES MUST BE COORDINATED WITH THE OWNER. NOTICE OF OUTAGES MUST BE GIVEN NO LATER THAN 7 DAYS PRIOR TO THE EVENT. THE CONTRACTOR SHALL GET APPROVAL FROM THE OWNER FOR POWER OUTAGES.
- C. A MAXIMUM OF 8 HOURS SHALL BE ALLOWED FOR POWER OUTAGE NO. 1 WHICH WILL AFFECT ALL POWER TO THE PLANT. CONTRACTOR SHALL HAVE A PORTABLE GENERATOR ON SITE OF SUFFICIENT SIZE TO POWER THE PLANT IN THE EVENT THE OUTAGE LASTS MORE THAN EIGHT HOURS.
- D.A MAXIMUM OF 24 HOURS SHALL BE ALLOWED FOR POWER OUTAGE NO. 2 FOR MCC-E. A MAXIMUM OF 48 HOURS SHALL BE ALLOWED FOR ALL OTHER POWER OUTAGES, UNLESS OTHERWISE NOTED. CONTRACTOR SHALL HAVE A PORTABLE GENERATOR ON SITE OF SUFFICIENT SIZE TO POWER THE DESIGNATED LOAD IN THE EVENT THE OUTAGE LASTS MORE THAN THE DESIGNATED TIME.
- E. CONTRACTOR SHALL HAVE ALL EQUIPMENT AND MATERIALS ON SITE BEFORE TAKING THE EXISTING ELECTRICAL DISTRIBUTION SYSTEM OUT OF SERVICE. OWNER SHALL HAVE FINAL SAY IF THE ELECTRICAL DISTRIBUTION SYSTEM CAN BE TAKEN OUT OF SERVICE.
- F. THE FOLLOWING IS A SUGGESTED SEQUENCE OF CONSTRUCTION FOR THE UPGRADES TO THE ELECTRICAL DISTRIBUTION SYSTEM.
- 1. INSTALL CONCRETE PAD AND CONDUITS AS REQUIRED FOR PMG-1 FEEDER BAY.
- 2. EXTEND 5 KV DUCTBANK FROM PMG-1 FEEDER BAY TO LOCATION OF NEW 5 KV PAD MOUNTED SWITCH PMG-2.
- 3. EXCAVATE AND INSTALL CONDUITS AS REQUIRED FOR PMG-2, TRANSFORMER T-2 AND SWITCHBOARD MSWB-1. POUR CONCRETE PAD.
- 4. INSTALL PMG-2, TRANSFORMER T-2, AND SWITCHBOARD MSWB-1. INSTALL CONDUCTORS FROM PMG-2 TO TRANSFORMER T-2 TO SWITCHBOARD MSWB-1. TERMINATE ALL CABLES AND PREPARE TO ENERGIZE EQUIPMENT.
- 5. <u>POWER OUTAGE NO. 1</u> OPEN EXISTING MAIN SWITCH IN 5 KV SWITCHGEAR PMG—1. INSTALL FEEDER BAY ON EXISTING PMG-1 AND CONNECT FEEDER BAY BUS TO EXISTING BUS. CLOSE MAIN SWITCH TO RE-ENERGIZE PMG-1 (PLEASE NOTE THAT NEW FEEDER BAY SWITCH SHALL REMAIN OPEN).
- 6. INSTALL 5 KV CABLES FROM PMG-1 FEEDER BAY TO NEW 5 KV PAD MOUNTED SWITCH PMG-2. TERMINATE CABLES AND ENERGIZE PMG-2, TRANSFORMER T-2 AND SWITCHBOARD MSWB-1.
- 7. INSTALL CONDUITS AND CONDUCTORS AS REQUIRED FROM MSWB-1 TO MCC-E.

SYMBOL LIST (CONT. **ABBREVIATIONS**

A BKR	AMPERES BREAKER	•	LOCAL CONTROL STATION
C G HH	CONDUIT GROUND HANDHOLE	R	WALL MOUNTED YELLOW AND RED WARNING LIGHT
HV KV	HIGH VOLTAGE KILO-VOLTS KILO-VOLT AMPERES	G	GAS DETECTION SENSOR
KVA LV MCP	LOW VOLTAGE MOTOR CONTROL PROTECTOR	$\mathbb{H} \triangleleft$	GAS DETECTION ALARM HORN
MH PH	MANHOLE PHASE	TS	THERMAL SWITCH
RAS WAS	RETURN ACTIVATED SLUDGE WASTE ACTIVATED SLUDGE	PS	PRESSURE SWITCH
VFD	VARIABLE FREQUENCY DRIVE	SV	SEAL WATER SOLENOID VALVE
SYN	MBOL LIST	—E-480V—	EXISTING 480V DUCTBANK
LIT	LEVEL INDICATING TRANSMITTER	480V	480V DUCTBANK
LS	LEVEL TRANSDUCER VALVE OPERATOR	——EDB——	EXISTING LOW VOLTAGE DUCTBANK
VO		——5KV——	5KV DUCTBANK
		——A-EDB——	ABANDON UNDERGROUND DUCTBANK
ر -	CIRCUIT BREAKER	M	MOTOR CONTACTOR
<u> </u>	FUSED SWITCH	—F—	FORWARD CONTACTOR
¥ ₹		$\overline{\mathbb{R}}$	REVERSE CONTACTOR
HWww-I	FEEDER CABLE		NORMALLY CLOSED CONTACT
	PANEL, SWITCHBOARD, MCC, OR VFD BUS	———	NORMALLY OPEN CONTACT
m m	TRANSFORMER		PUSH-TO-TEST GREEN INDICATING LIGHT
#	MOTOR, # INDICATES HORSEPOWER	—X—	THERMAL OVERLOAD
\otimes	COPPER GROUND ROD	þ	FUSE
	EQUIPMENT TO BE REMOVED	=	GROUND
4	DISCONNECT SWITCH		SELECTOR SWITCH
		ETM	

SUGGESTED SEQUENCE OF CONSTRUCTION (CONT.)

COMBINATION STARTER/DISCONNECT SWITCH

8. POWER OUTAGE NO. 2 - TURN OFF BREAKER IN EXISTING I-LINE PANELBOARD FEEDING EXISTING MCC-E DISCONNECT EXISTING FEEDER CONDUCTORS AT MCC-E. TERMINATE NEW CONDUCTORS TO EXISTING MCC-E MAIN BREAKER. TURN ON BREAKER IN MSWB-1 TO ENERGIZE MCC-E. REMOVE EXISTING CONDUCTORS PREVIOUSLY FEEDING MCC-E.

ELAPSED TIME METER

- 9. INSTALL CONDUITS AND CONDUCTORS AS REQUIRED FROM MSWB-1 TO THE VICINITY OF THE EXISTING C.B. ENGINE ROOM PANEL.
- 10. POWER OUTAGE NO. 3 TURN OFF BREAKER IN EXISTING I-LINE PANELBOARD FEEDING EXISTING C.B. ENGINE ROOM PANEL. DISCONNECT AND REMOVE EXISTING CONDUCTORS FEEDING PANEL. EXTEND CONDUITS TO PANEL AND INSTALL CONDUCTORS AS REQUIRED. TERMINATE CONDUCTORS TO EXISTING MAIN BREAKER IN PANEL. TURN ON BREAKER IN MSWB-1 TO ENERGIZE PANEL
- 11. EXCAVATE AND REMOVE EXISTING CONCRETE ENCASEMENT FROM EXISTING DUCTBANK FEEDING EXISTING MCC-B AS INDICATED. INSTALL DUCTBANK FROM MSWB-1 TO VICINITY OF EXISTING EXCAVATED DUCTBANK FEEDING MCC-B.
- 12. POWER OUTAGE NO. 4 TURN OFF BREAKER IN EXISTING I-LINE PANELBOARD FEEDING EXISTING MCC-B. DISCONNECT AND REMOVE EXISTING CONDUCTORS FEEDING MCC-B. CUT EXISTING 4" DUCT FEEDING MCC-B AND EXTEND DUCT TO INTERCEPT EXISTING DUCT AS INDICATED. INSTALL CONDUCTORS FROM MSWB-1 TO MCC-B AND TERMINATE CONDUCTORS. TURN ON BREAKER IN MSWB-1 TO ENERGIZE MCC-B.
- 13. EXCAVATE AND REMOVE EXISTING CONCRETE ENCASEMENT FROM EXISTING DUCTBANK FEEDING EXISTING MCC-C AS INDICATED. INSTALL DUCTBANK FROM MSWB-1 TO VICINITY OF EXISTING EXCAVATED DUCTBANK FEEDING MCC-C.
- 14. POWER OUTAGE NO. 5 TURN OFF EXISTING BREAKER IN EXISTING I-LINE PANELBOARD FEEDING EXISTING MCC-C. DISCONNECT AND REMOVE EXISTING CONDUCTORS FEEDING MCC-C. CUT EXISTING 4" DUCT FEEDING MCC-C AND EXTEND DUCT TO INTERCEPT EXISTING DUCT AS INDICATED. INSTALL CONDUCTORS FROM MSWB-1 TO MCC-C AND TERMINATE CONDUCTORS. TURN ON BREAKER IN MSWB-1 TO ENERGIZE MCC-C.
- 15. EXCAVATE AND REMOVE EXISTING CONCRETE ENCASEMENT FROM EXISTING DUCTBANK FEEDING EXISTING TRANSFORMER T-3 AS INDICATED. INSTALL DUCTBANK FROM PMG-2 TO VICINITY OF EXISTING EXCAVATED DUCTBANK FEEDING TRANSFORMER.
- 16. POWER OUTAGE NO. 6 OPEN EXISTING 5 KV SWITCH FEEDING TRANSFORMER T-3. DISCONNECT AND REMOVE EXISTING 5 KV CABLES FEEDING TRANSFORMER T-3. CUT EXISTING DUCT AND EXTEND DUCT TO INTERCEPT EXISTING DUCT AS INDICATED. INSTALL 5 KV CABLES FROM PMG-2 TO TRANSFORMER T-3 AND TERMINATE CABLES. CLOSE 5 KV SWITCH IN PMG-2 TO ENERGIZE TRANSFORMER T-3.
- 17. AFTER EQUIPMENT HAS BEEN RE-ENERGIZED, CONCRETE ENCASE DUCTS AND BACKFILL TRENCHES AS REQUIRED.

IOIS STEF ILLING DIGES ENTS Y OF . SIDE CITA

ENGINEERS

DESIGN FIRM REGISTRATIO No. 184-000450 1817 SOUTH NEIL STREET SUITE 100 CHAMPAIGN, ILLINOIS (217) 373-8900 (217) 373-8923

DESIGNED BY: DRAWN BY: DRAWN BY:

CHECKED BY:

CEC/SEM DATE CHECKED: 07/06 NOTE: DIMENSIONAL DATA IS NOT TO BE OBTAINED BY

SCALING ANY PORTION OF

THIS DRAWING.

REVISION

PROJECT No. J02570


DRAWING TITLE


0 OTE AP B SYN \mathcal{O}

> DRAWING No E-.

Ш

DRAWING 21 OF 41





ELECTRICAL NOTES (THIS DRAWING)

- 1. SEE DRAWING E-21 FOR ENLARGED PLAN OF PAD MOUNTED ELECTRICAL EQUIPMENT.
- 2. SEE DRAWING E-5 FOR MSWB-1 ELEVATION AND SCHEDULE.
- 3. SEE DRAWING E-20 FOR DUCTBANK SECTIONS AND DUCTBANK CABLE SCHEDULE.
- 4. SEE DRAWING E-1 FOR GENERAL NOTES, SYMBOL LIST AND SUGGESTED SEQUENCE OF CONSTRUCTION.

KEYNOTES (THIS DRAWING)

- 1 EXISTING UNDERGROUND DUCTBANK TO REMAIN.
- REMOVE EXISTING PAD MOUNTED 5KV SWITCHES PMG-2 AND CONCRETE PADS. REMOVE EXISTING 5KV CONDUCTORS FEEDING PMG-2 BACK TO 5KV SWITCHGEAR IN BLOWER BUILDING (SEE DRAWING E-10). REMOVE UNDERGROUND CONDUITS TO HV MANHOLE.
- REMOVE EXISTING TRANSFORMER T-2 AND CONCRETE PAD. REMOVE ASSOCIATED UNDERGROUND CONDUITS/CONDUCTORS BACK TO PMG-2.
- REMOVE EXISTING SQUARE D 800A, 480V, 3Ø, 3W, MLO I-LINE PANELBOARD, CONCRETE PAD, AND ASSOCIATED UNDERGROUND CONDUITS/CONDUCTORS BACK TO TRANSFORMER T-2.
- (5) EXISTING HV MANHOLE TO REMAIN.
- 6 EXISTING LV MANHOLE MH3 TO REMAIN.
- $\langle 7 \rangle$ PROVIDE 5KV PAD MOUNTED SWITCH PMG-2.
- $\langle 8 \rangle$ PROVIDE CONCRETE ENCASED DUCTBANK FROM FEEDER BAY ON PMG-1 TO PMG-2.
- 9 PROVIDE TRANSFORMER T-2. PROVIDE (2) 3 1/2"C, 1 SPARE AND 1 WITH 3#2 (5KV) FROM TRANSFORMER TO PMG-2.
- PROVIDE SWITCHBOARD MSWB-1. SEE DRAWING E-5 FOR ELEVATION AND SCHEDULE. EXTEND (4) 3"C, 1 SPARE AND OTHER (3) CONDUITS EACH WITH 3#500, 1#3/0G TO TRANSFORMER T-2.
- $\langle 11 \rangle$ PROVIDE 6" DIAMETER CONCRETE FILLED PIPE BOLLARD. SEE DRAWING E-21 FOR DETAIL.
- 12 INTERCEPT (2) EXISTING 4" DUCTS FEEDING EXISTING TRANSFORMER T-3 (SEE DRAWING E-2 FOR LOCATION) AND EXTEND TO NEW PMG-2.
- (13) INTERCEPT EXISTING 4" DUCT FEEDING MCC-C AND EXTEND TO NEW MSWB-1.
- EXISTING UNDERGROUND DUCTBANK TO BE ABANDONED IN PLACE (REMOVE CONDUCTORS FROM MH3 TO C.B. ENGINE ROOM PANEL).
- (15) PROVIDE CONCRETE ENCASED DUCTBANK TO TUNNEL. PENETRATE TUNNEL WALL AND ROUTE CONDUITS TO EXISTING C.B. ENGINE ROOM PANEL AND MCC-E (SEE KEYNOTE 23).
- EXISTING UNDERGROUND DUCTBANK TO BE ABANDONED IN PLACE (REMOVE CONDUCTORS FROM MH3 TO MCC-C).
- $\langle 17 \rangle$ EXISTING UNDERGROUND DUCTBANK TO REMAIN AND BE REUSED.
- $\langle 18 \rangle$ PROVIDE CONCRETE PAD. SEE DRAWING E-21 FOR DETAILS.
- PROVIDE CONCRETE ENCASED DUCTBANK FROM PMG-2 TO EXISTING DUCTS (SEE KEYNOTE 12). REPLACE EXISTING 5KV CABLES FROM EXISTING PMG-2 TO EXISTING TRANSFORMER T-3 WITH NEW FROM PMG-2 TO EXISTING TRANSFORMER T-3.
- $\langle 20 \rangle$ INTERCEPT EXISTING 4" DUCT FEEDING MCC-B AND EXTEND TO MSWB-1.
- (21) EXISTING HANDHOLE HH1.
- (22) REMOVE CONDUITS AND CONDUCTORS IN EXISTING TUNNEL TO C.B. ENGINE ROOM PANEL.
- PROVIDE (4) 3 1/2" RGS CONDUITS, (2) CONDUITS EACH WITH 3#350, 1#1G TO EXISTING C.B. ENGINE ROOM PANEL AND (2) CONDUITS EACH WITH 3#350, 1#2G TO EXISTING MCC-E.
- REMOVE UNDERGROUND CONDUITS AND CONDUCTORS (PLUG OPENINGS IN MANHOLE AFTER CONDUITS ARE REMOVED).

PROJECT INFORMATION

CITY OF JOLIET, ILLINOIS
ASTSIDE WWTP DIGESTER
IMPROVEMENTS



DESIGN FIRM REGISTRATIO
No. 184-000450

1817 SOUTH NEIL STREET
SUITE 100
CHAMPAIGN, ILLINOIS
(217) 373-8900
(217) 373-8923

DESIGNED BY: JJF
DRAWN BY: RSL
CHECKED BY: CEC/SEM
DATE CHECKED: 07/06

NOTE: DIMENSIONAL DATA IS

NOT TO BE OBTAINED BY SCALING ANY PORTION OF

THIS DRAWING.

DEVIZORON

J02570

DRAWING TITLE

NLARGED ELECTRICA SITE PLAN

E-3

DRAWING 23 OF 41

Mon, 07 Aug 2006 — 4:32pm Last Edited By: CHL Drawing Name: P:\J102570\Jolist Eastside Studge\ELEC\E—3 (enlarged).dug


				PROCESS N	иотоғ	R SCHEDULE								
	EQUIPMENT			MOTOR			POWER					CONTROLLER		
NAMEPLATE DESCRIPTION	TAG	STATUS	LOCATION	HP VOLT	PHA	ASE EXIST. SOURCE	NEW SOURCE	CONDU	IIT CONDUCTOR	TYPE	SIZE	LOCATION	DIAGRAM	NOTES
PRIMARY TANK NO. 1 MAIN GEAR DRIVE	PST-101	REPLACE - 1/2 HP	PRIMARY TANKS	1/2 460	3	MCC-E	MCC-E	3/4"	3#12, 1#12G	FVR	1	MCC-E	TYPE 1	SEE NOTE 3
PRIMARY TANK NO. 1 CROSS COLLECTOR DRIVE	PST-101A	NEW	PRIMARY TANKS	1/3 460	3	3 N/A	MCC-E	3/4"	3#12, 1#12G	FVR	1	MCC-E	TYPE 1	SEE NOTE 3
PRIMARY TANK NO. 2 MAIN GEAR DRIVE	PST-102	REPLACE - 1/2 HP	PRIMARY TANKS	1/2 460	7	MCC-E	MCC-E	3/4"	3#12, 1#12G	FVR	1	MCC-E	TYPE 1	SEE NOTE 3
PRIMARY TANK NO. 2 CROSS COLLECTOR DRIVE	PST-102A	NEW	PRIMARY TANKS	1/3 460	3	3 N/A	MCC-E	3/4"	3#12, 1#12G	FVR	1	MCC-E	TYPE 1	SEE NOTE 3
PRIMARY TANK NO. 3 MAIN GEAR DRIVE	PST-103	REPLACE - 1/2 HP	PRIMARY TANKS	1/2 460	3	MCC-E	MCC-E	3/4"	3#12, 1#12G	FVR	1	MCC-E	TYPE 1	SEE NOTE 3
PRIMARY TANK NO. 3 CROSS COLLECTOR DRIVE	PST-103A	NEW	PRIMARY TANKS	1/3 460	7	3 N/A	MCC-E	3/4"	3#12, 1#12G	FVR	1	MCC-E	TYPE 1	SEE NOTE 3
PRIMARY TANK NO. 4 MAIN GEAR DRIVE	PST-104	REPLACE - 1/2 HP	PRIMARY TANKS	1/2 460	7	MCC-E	MCC-E	3/4"	3#12, 1#12G	FVR	1	MCC-E	TYPE 1	SEE NOTE 3
PRIMARY TANK NO. 4 CROSS COLLECTOR DRIVE	PST-104A	NEW	PRIMARY TANKS	1/3 460	7	3 N/A	MCC-E	3/4"	3#12, 1#12G	FVR	1	MCC-E	TYPE 1	SEE NOTE 3
				,				,	" "					
RAW SLUDGE PUMP NO. 1	RSP-1	REPLACE - 20 HP	CONTROL BUILDING	30 460	7	3 CB ENGINE ROOM PNL	CB ENGINE ROOM PNL	1"	3#6, 1#8G	FVNR	3	NEAR MOTOR	TYPE 2	SEE NOTE 2
RAW SLUDGE PUMP NO. 2	RSP-2	REPLACE - 20 HP	CONTROL BUILDING	30 460	7	3 CB ENGINE ROOM PNL	CB ENGINE ROOM PNL	1"	3#6, 1#8G	FVNR	3	NEAR MOTOR	TYPE 2	SEE NOTE 2
									" "					
RETURN ACTIVATED SLUDGE PUMP NO. 1	P-331	REPLACE - 50 HP	BLOWER BUILDING	40 460	7	MCC-D	MCC-D	1"	3#4, 1#8G	VFD	40 HP	NEAR MOTOR		SEE NOTE 3
RETURN ACTIVATED SLUDGE PUMP NO. 2	P-332	REPLACE - 50 HP	BLOWER BUILDING	40 460	7	MCC-D	MCC-D	1"	3#4, 1#8G	VFD	40 HP	NEAR MOTOR		SEE NOTE 3
RETURN ACTIVATED SLUDGE PUMP NO. 3	P-333	REPLACE - 50 HP	BLOWER BUILDING	40 460	7	MCC-D	MCC-D	1"	3#4, 1#8G	VFD	40 HP	NEAR MOTOR		SEE NOTE 3
RETURN ACTIVATED SLUDGE PUMP NO. 4	P-334	REPLACE - 50 HP	BLOWER BUILDING	40 460	7	MCC-D	MCC-D	1"	3#4, 1#8G	VFD	40 HP	NEAR MOTOR		SEE NOTE 3
									" "					
ACTIVATED SLUDGE TANK DRAINAGE PUMP NO. 1	P-335	REPLACE - 7 1/2 HP	BLOWER BUILDING	7 1/2 460	3	MCC-D	MCC-D	3/4"	3#12, 1#12G	FVNR	1	MCC-D	TYPE 3	SEE NOTE 3
ACTIVATED SLUDGE TANK DRAINAGE PUMP NO. 2	P-336	REPLACE - 7 1/2 HP	BLOWER BUILDING	7 1/2 460	7	MCC-D	MCC-D	3/4"	3#12, 1#12G	FVNR	1	MCC-D	TYPE 3	SEE NOTE 3
								,						
WASTE ACTIVATED SLUDGE PUMP NO. 1	P-313	REPLACE - 10 HP	AERATION PIPE GALLERY	20 460		MCC-D/CONTROL PNL	MCC-D	3/4"	3#8, 1#10G	FVNR	2	MCC-D	TYPE 3	SEE NOTE 2
WASTE ACTIVATED SLUDGE PUMP NO. 2	P-314	REPLACE - 10 HP	AERATION PIPE GALLERY	20 460	7	MCC-D/CONTROL PNL	MCC-D	3/4"	3#8, 1#10G	FVNR	2	MCC-D	TYPE 3	SEE NOTE 2
WASTE ACTIVATED SLUDGE PUMP NO. 3	P-315	REPLACE - 10 HP	AERATION PIPE GALLERY	20 460	- 3	MCC-D/CONTROL PNL	MCC-D	3/4"	3#8, 1#10G	FVNR	2	MCC-D	TYPE 3	SEE NOTE 2
DIGESTER MIXING PUMP NO. 1	P-721	NEW	DIGESTER BUILDING	60 460	7	3 N/A	MCC-B	1 1/4"	3#1, 1#6G	FVNR	4	MCC-B	TYPE 4	SEE NOTE 3
DIGESTER MIXING PUMP NO. 2	P-722	NEW	DIGESTER BUILDING	60 460	7	3 N/A	MCC-B	1 1/4"	3#1, 1#6G	FVNR	4	MCC-B	TYPE 4	SEE NOTE 3
PRIMARY DIGESTER NO. 1 SUCTION VALVE ACTUATOR	MOV-731A	NEW	DIGESTER BUILDING	1 AMP 460		3 N/A	DIGESTER CONTROL PNL	3/4"	3#12, 1#12G	MFR. PANEL	N/A	ON ACTUATOR		SEE NOTE 3
PRIMARY DIGESTER NO. 1 DISCHARGE VALVE ACTUATOR	MOV-731B	NEW	DIGESTER BUILDING	1 AMP 460		3 N/A	DIGESTER CONTROL PNL	3/4"	3#12, 1#12G	MFR. PANEL	N/A	ON ACTUATOR		SEE NOTE 3
PRIMARY DIGESTER NO. 2 SUCTION VALVE ACTUATOR	MOV-732A	NEW	DIGESTER BUILDING	1 AMP 460	3	3 N/A	DIGESTER CONTROL PNL	3/4"	3#12, 1#12G	MFR. PANEL	N/A	ON ACTUATOR		SEE NOTE 3
PRIMARY DIGESTER NO. 2 DISCHARGE VALVE ACTUATOR	MOV-732B	NEW	DIGESTER BUILDING	1 AMP 460	7	3 N/A	DIGESTER CONTROL PNL	3/4"	3#12, 1#12G	MFR. PANEL	N/A	ON ACTUATOR		SEE NOTE 3
PRIMARY DIGESTER NO. 3 SUCTION VALVE ACTUATOR	MOV-733A	NEW	DIGESTER BUILDING	1 AMP 460	7	3 N/A	DIGESTER CONTROL PNL	3/4"	3#12, 1#12G	MFR. PANEL	N/A	ON ACTUATOR		SEE NOTE 3
PRIMARY DIGESTER NO. 3 DISCHARGE VALVE ACTUATOR	MOV-733B	NEW	DIGESTER BUILDING	1 AMP 460	3	3 N/A	DIGESTER CONTROL PNL	3/4"	3#12, 1#12G	MFR. PANEL	N/A	ON ACTUATOR		SEE NOTE 3
GRAVITY BELT THICKENER SLUDGE PUMP NO. 1	P-601	REPLACE - 20 HP	SOLIDS PROCESSING BLDG.	40 460	7	MCC-A	MCC-A	1"	3#4, 1#8G	FVNR	3	MCC-A	TYPE 3	SEE NOTE 2
GRAVITY BELT THICKENER SLUDGE PUMP NO. 2	P-602	REPLACE - 30 HP	SOLIDS PROCESSING BLDG.	40 460	7	MCC-A	MCC-A	1"	3#4, 1#8G	FVNR	3	MCC-A	TYPE 3	SEE NOTE 2
GRAVITY BELT THICKENER SLUDGE PUMP NO. 3	P-603	REPLACE - 30 HP	SOLIDS PROCESSING BLDG.	40 460	- 3	MCC-A	MCC-A	1"	3#4, 1#8G	FVNR	3	MCC-A	TYPE 3	SEE NOTE 2
SLUDGE SUPERNATANT LINE VALVE ACTUATOR	MOV-321	NEW	PARSHALL FLUME	1 AMP 460	3	3 N/A	480V PANEL PP1	3/4"	3#12, 1#12G	MFR. PANEL	N/A	ON ACTUATOR		SEE NOTE 3

PROCESS MOTOR SCHEDULE NOTES:

REUSE EXISTING CONDUIT AND PROVIDE NEW WIRE.

REUSE EXISTING CONDUIT AND EXTEND TO EQUIPMENT AS REQUIRED. PROVIDE NEW WIRE.

PROVIDE NEW CONDUIT AND WIRE.



DESIGNED BY: ___ DRAWN BY: RSL
CHECKED BY: CEC/SEM DATE CHECKED: ____07/06_ NOTE: DIMENSIONAL DATA IS NOT TO BE OBTAINED BY SCALING ANY PORTION OF THIS DRAWING.

, ILLINOIS DIGESTEF ENTS

Y OF JOLIET, I ISIDE WWTP I

CITA

ENGINEERS DESIGN FIRM REGISTRATION No. 184-000450 1817 SOUTH NEIL STREET SUITE 100 CHAMPAIGN, ILLINOIS (217) 373-8900 (217) 373-8923

DATE REVISION PROJECT No.


> J02570 DRAWING TITLE


> > PROCESS MOTOR SCHEDULE AND CONTROL DIAGRAMS


DRAWING No.

DRAWING 24 OF 41

E-4









ELECTRICAL NOTES (THIS DRAWING)

1817 SOUTH NEIL STREET SUITE 100 CHAMPAIGN, ILLINOIS (217) 373-8900 (217) 373-8923


NOTE: DIMENSIONAL DATA IS NOT TO BE OBTAINED BY SCALING ANY PORTION OF THIS DRAWING.








BASEMENT ELECTRICAL DEMOLITION PLAN





BASEMENT ELECTRICAL PROPOSED PLAN



ELECTRICAL NOTES (THIS DRAWING)

- 1. SEE DRAWING E-1 FOR GENERAL NOTES, SYMBOL LIST AND SUGGESTED SEQUENCE OF CONSTRUCTION.
- 2. SEE PROCESS MOTOR SCHEDULE ON DRAWING E-4 FOR ADDITIONAL INFORMATION ON MOTOR LOADS.
- 3. SEE DRAWING E-11 FOR VFD SCHEDULE.

DEMOLITION KEYNOTES (THIS DRAWING)

- DISCONNECT EXISTING RAS PUMP AND ASSOCIATED SPEED CONTROL UNIT. REMOVE CONDUCTORS AND CONDUITS BACK TO SOURCE. EXISTING RAS PUMPS ARE FED FROM MCC-D (SEE DRAWING E-10 FOR LOCATION).
- 2 DISCONNECT EXISTING ACTIVATED SLUDGE TANK DRAINAGE PUMPS. REMOVE CONDUCTORS AND CONDUITS BACK TO MCC-D (SEE DRAWING E-10 FOR LOCATION.)

KEYNOTES (THIS DRAWING)

- $\langle 1 \rangle$ RAS PUMP NO.2 (P-332) AND VFD.
- $\langle 2 \rangle$ RAS PUMP NO.3 (P-333) AND VFD.
- $\overline{3}$ RAS PUMP NO.1 (P-331) AND VFD.
- $\langle 4 \rangle$ RAS PUMP NO.4 (P-334) AND VFD.
- $\langle 5 \rangle$ ACTIVATED SLUDGE TANK DRAINAGE PUMP NO.1 (P-335).
- 6 ACTIVATED SLUDGE TANK DRAINAGE PUMP NO.2 (P-336).
- PROVIDE 30A, 3 POLE, HEAVY DUTY NON-FUSIBLE DISCONNECT SWITCH IN NEMA 12 ENCLOSURE FOR ACTIVATED SLUDGE TANK DRAINAGE PUMP NO.1.
- 8 PROVIDE 30A, 3 POLE, HEAVY DUTY NON-FUSIBLE DISCONNECT SWITCH IN NEMA 12 ENCLOSURE FOR ACTIVATED SLUDGE TANK DRAINAGE PUMP NO.2.
- (9) START/STOP LOCAL CONTROL STATION.

CITY OF JOLIET, ILLINOIS EASTSIDE WWTP DIGESTER IMPROVEMENTS



ENGINEERS
DESIGN FIRM REGISTRATION
No. 184-000450 1817 SOUTH NEIL STREET SUITE 100 CHAMPAIGN, ILLINOIS (217) 373-8900

(217) 373-8923

DESIGNED BY: CHECKED BY: CEC/SEM DATE CHECKED: ____07/06 NOTE: DIMENSIONAL DATA IS NOT TO BE OBTAINED BY


THIS DRAWING.

SCALING ANY PORTION OF

J02570 DRAWING TITLE

BLOWER BUILDING BASEMENT ELECTRICAL PLANS

<u>KEY PLAN</u> <u>BLOWER BUILDING</u>



1817 SOUTH NEIL STREET CHAMPAIGN, ILLINOIS

NOT TO BE OBTAINED BY SCALING ANY PORTION OF

4 A 10A 12A 1B 3B 10B 12B 11B 1C 3C 1 1 $\langle 1 \rangle$ $|1\rangle$ 1D 3D $\langle 1 \rangle$ $\langle 1 \rangle$ $\langle 2 \rangle 2$ 1 $\langle 2 \rangle 2$ $\langle 3 \rangle$

> MCC-D ELEVATION E-10 E-11

	VARIABLE FREQUENCY DRIVE SCHEDULE																																
														ACCESSORIES						INPUTS/OUTPUTS						ENCLOSURE							
							RIABLE TORQUE VFD	CONSTANT TORQUE VFD	MAN INTERFACE MODULE	MOTOR ELAPSED TIME METER	SIBLE DISCONNECT SWITCH	MANUAL BYPASS STARTER	D MANUAL SPEED CONTROL	'0/A SWITCH	CONTROL POWER ON" LIGHT	GREEN "RUN" LIGHT	ULT RESET	IARMONIC GUARD TRAP FILTER	INPUT REACTOR EXTERNALLY MOUNTED OUTPUT LINE REACTOR	START PUSHBUTTON	STOP PUSHBUTTON	D/BYPASS	UTO" POSITION	D FAULT	"HAND" POSITION	D RUNNING	REMOTE START/STOP	MOTOR THERMAL SWITCH	AL WATER SOLENOID VALVE	D SPEED (ANALOG INPUT)	D SPEED (ANALOG OUTPUT)	MA 1 ENCLOSURE	MA 12 ENCLOSURE
EQUIPMENT TAG	HP	AMPS	VOLTAGE	PHASE	RPM	LOCATION	VARI	8	MUH	O W	FUSII	M	VFD	′0/н	Š	GR	FAUL	H	INPU. EXTE	ST,	ST	VFD,	"AU	VFD	Ĭ,	VFD	REI	OΨ	SE,	VFD	VFI	NEW	NEW
RAS PUMP NO.1	40	52	460	3	880	BLOWER BUILDING	X		X	X	X		X	X	X	X	X		X	X	X		X	X	×	X	X	X	X	X	X		X
RAS PUMP NO.2	40	52	460	3	880	BLOWER BUILDING	X		X	Х	X		Х	X	Х	Х	Х		Х	X	Х		Х	Х	Х	X	Х	X	X	Х	Х		X
RAS PUMP NO.3	40	52	460	3	880	BLOWER BUILDING	Х		Х	Х	Х		Х	Х	Х	Х	Х		Х	X	Х		Х	Х	Х	Х	X	Х	Χ	Χ	Х		X
RAS PUMP NO.4	40	52	460	3	880	BLOWER BUILDING	Х		Х	X	Х		Χ	Х	Х	Х	Χ		Х	Х	Х		Х	Χ	Х	Х	Х	Х	X	Χ	Х		X

- 1. SEE SPECIFICATION SECTION 16483 VARIABLE FREQUENCY DRIVES FOR MORE DETAILS.
 2. THE OUTPUTS FOR AUTO POSITION, HAND POSITION, FAULT, RUNNING, VFD/BYPASS, AND REMOTE START/STOP SHALL BE DRY CONTACTS RATED FOR 10A, 120V.
 3. CONTRACTOR TO PROVIDE DRY RELAY CONTACTS FOR ALL MOTOR RUN AND FAIL SIGNALS.

ELECTRICAL NOTES (THIS DRAWING)

- 1. SEE DRAWING E-1 FOR GENERAL NOTES, SYMBOL LIST AND SUGGESTED SEQUENCE OF CONSTRUCTION.
- 2. SEE PROCESS MOTOR SCHEDULE ON DRAWING E-4 FOR ADDITIONAL INFORMATION ON MOTOR LOADS.

DEMOLITION KEYNOTES (THIS DRAWING)

- 1 REMOVE EXISTING RAS PUMP STARTER.
- 2 REMOVE EXISTING ACTIVATED SLUDGE PUMP STARTER.
- 3 ABANDON IN PLACE EXISTING CIRCUIT BREAKER FOR WAS PUMP. LABEL AS

KEYNOTES (THIS DRAWING)

- RECONFIGURE BUCKET TO ACCEPT 110A, 3 POLE CIRCUIT BREAKER TO FEED NEW RAS PUMP VFD.
- PROVIDE NEMA SIZE 1 COMBINATION STARTER WITH 20A MCP FOR ACTIVATED SLUDGE TANK DRAINAGE PUMP. RECONNECT EXISTING CONTROL WIRING AS REQUIRED TO STARTER.
- PROVIDE NEMA SIZE 2 COMBINATION STARTER WITH 60A MCP FOR WAS
- 4 PROVIDE BLANK DOOR FOR EMPTY CUBICLE.

CITY OF JOLIET, ILLINOIS EASTSIDE WWTP DIGESTER IMPROVEMENTS

ENGINEERS
DESIGN FIRM REGISTRATION No. 184-000450 1817 SOUTH NEIL STREET SUITE 100 CHAMPAIGN, ILLINOIS (217) 373-8900

(217) 373-8923

CHECKED BY: CEC/SEM DATE CHECKED: ____07/06__ NOTE: DIMENSIONAL DATA IS NOT TO BE OBTAINED BY SCALING ANY PORTION OF

THIS DRAWING.


J02570

E-11

	4#14 (2 SPARE), 1#14G (C)	SV	SEAL WATER
	4#14 (2 SPARE), 1#14G (C)		SOLENOID VALVE MOTOR THERMAL
	<i>"</i>	- TS	SWITCH
	3#4, 1#8G (P)		BREAKER IN EXISTING MCC-D
VED	3#4, 1#8G (P)	-	RAS PUMP
<u>VFD</u>	(2) 2#18 TSP CABLES (A)		
] 16#14 (6 SPARE), 1#14G (C)		EXISTING CONTROL PANEL

RAS PUMP VFD INTERCONNECT DIAGRAM

-EXISTING CONCRETE FLOOR




ELECTRICAL NOTES (THIS DRAWING) CITY OF JOLIET, ILLINOIS EASTSIDE WWTP DIGESTER IMPROVEMENTS 1. SEE DRAWING E-1 FOR GENERAL NOTES, SYMBOL LIST AND SUGGESTED SEQUENCE OF CONSTRUCTION. 2. SEE DRAWING E-15 FOR LOCATION OF 120V PANEL LP-B AND CONTROL PANEL 3. SEE DRAWING PR-15 FOR SECTION VIEW OF WASTE GAS BURNER AND ASSOCIATED PIPING AND CONTROL PANEL. DEMOLITION KEYNOTES (THIS DRAWING) 1 REMOVE ALL ELECTRICAL ASSOCIATED WITH WASTE GAS BURNERS. REMOVE ALL CONDUIT AND WIRE BACK TO SOURCE (ABANDON UNDERGROUND CONDUITS IN PLACE). KEYNOTES (THIS DRAWING) PROVIDE 2#12, 1#12G, 1"C (120V POWER) UNDERGROUND FROM WASTE GAS BURNER CONTROL PANEL TO PANEL LP-B. PROVIDE 12#14 (4 SPARE), 1#14G, 1"C (CONTROL) FROM WASTE GAS BURNER CONTROL PANEL TO EXISTING CONTROL PANEL SCC-B. WASTE GAS BURNER CONTROL PANEL. PROVIDE 1" CONDUIT WITH MANUFACTURER PROVIDED HIGH TENSION CABLE AND THERMOCOUPLE WIRING FROM WASTE GAS BURNER CONTROL PANEL TO MANUFACTURER ENGINEERS
DESIGN FIRM REGISTRATION
No. 184-000450 PROVIDED JUNCTION BOX MOUNTED ON WASTE GAS BURNER. ROUTE CONDUIT WITH PRIMARY DIGESTER NO. 3 WASTE GAS PIPING ABOVE GROUND. PRIMARY DIGESTER NO. 1 (733) 1817 SOUTH NEIL STREET (731) SUITE 100 CHAMPAIGN, ILLINOIS (217) 373-8900 4 WASTE GAS BURNER. (217) 373-8923 DIGESTER BUILDING SEE DRAWINGS E-14 AND E-15 DRAWN BY: RSL
CHECKED BY: CEC/SEM
DATE CHECKED: 07/06 NOTE: DIMENSIONAL DATA IS NOT TO BE OBTAINED BY SCALING ANY PORTION OF THIS DRAWING. PRIMARY DIGESTER NO. 2 SECONDARY DIGESTER J02570 DIGESTER ENLARGED ELECTRICAL PLAN E-13

ELECTRICAL NOTES (THIS DRAWING) DEMOLITION KEYNOTES (THIS DRAWING) KEYNOTES (THIS DRAWING) CITY OF JOLIET, ILLINOIS ASTSIDE WWTP DIGESTER IMPROVEMENTS 1 DIGESTER MIXING PUMP NO.1 (P-721). 1 DISCONNECT AND REMOVE ELECTRICAL DISCONNECT SWITCH AND SEE DRAWING E-1 FOR GENERAL NOTES, SYMBOL LIST AND SUGGESTED SEQUENCE OF CONSTRUCTION. ASSOCIATED CONDUIT AND WIRING BACK TO MCC-B (SEE DRAWING DIGESTER MIXING PUMP NO.2 (P-722). E-16 FOR LOCATION). 2. SEE PROCESS MOTOR SCHEDULE ON DRAWING E-4 FOR ADDITIONAL INFORMATION ON MOTOR LOADS. ZONE 1 GAS DETECTION SENSORS. MOUNT HYDROGEN SENSOR 3' AFF, MOUNT OXYGEN SENSOR 5' AFF, MOUNT LEL SENSOR 2' BELOW 3. ALL WIRING, CONDUIT, AND ELECTRICAL EQUIPMENT IN THE CEILING. SEE DRAWING E-16 FOR GAS DETECTION INTERCONNECT DIAGRAM. PRIMARY DIGESTER BUILDING BASEMENT SHALL BE RATED FOR USE IN CLASS 1, DIVISION 2, GROUP D LOCATION PER THE 2005 NATIONAL ELECTRICAL CODE. PROVIDE SEAL-OFF FITTINGS PRIMARY DIGESTER BUILDING BASEMENT GAS DETECTION ALARM HORN. REQUIRED FOR ALL CONDUIT AND WIRE ENTERING OR LEAVING MOUNT HORN 8' AFF. THIS AREA. (6) OPEN/STOP/CLOSE LOCAL CONTROL STATIONS FOR PRIMARY DIGESTER SUCTION AND DISCHARGE VALVE ACTUATORS. START/STOP LOCAL CONTROL STATION FOR DIGESTER MIXING PUMP NO.1 AND NO.2. ENGINEERS

DESIGN FIRM REGISTRATION
No. 184-000450 (217) 373-8923 PRIMARY PRIMARY DIGESTER DIGESTER NO. 1 (731) NO. 1 (731) <u>CP-12</u> <u>CP-13</u> __MOV-731A −<u>MOV−733A</u> -<u>MOV-732A</u> <u>MOV-733B</u>-__<u>MOV-732B</u> vo ps vo MOV-731B7 NOTE: DIMENSIONAL DATA IS NOT TO BE OBTAINED BY SCALING ANY PORTION OF THIS DRAWING. J02570 PRIMARY DIGESTER NO. 2 (732) PRIMARY DIGESTER NO. 2 (732) BASEMENT ELECTRICAL DEMOLITION PLAN BASEMENT ELECTRICAL PROPOSED PLAN E-14

1817 SOUTH NEIL STREET SUITE 100 CHAMPAIGN, ILLINOIS (217) 373-8900

DRAWN BY: RSL
CHECKED BY: CEC/SEM
DATE CHECKED: 07/06



1817 SOUTH NEIL STREET CHAMPAIGN, ILLINOIS


ALL WIRING, CONDUIT, AND ELECTRICAL EQUIPMENT IN THE PRIMARY DIGESTER BUILDING BASEMENT AND IN AREAS WITH GAS HANDLING EQUIPMENT SHALL BE RATED FOR USE IN CLASS 1, DIVISION 2, GROUP D LOCATION PER THE 2005 NATIONAL ELECTRICAL CODE. PROVIDE SEAL-OFF FITTINGS REQUIRED FOR ALL CONDUIT AND WIRE ENTERING OR LEAVING THIS AREA.

DEMOLITION KEYNOTES (THIS DRAWING)


- 1 DISCONNECT AND REMOVE WIRING TO EXISTING STARTER FOR CP-13. LABEL STARTER AS SPARE.
- 2 DISCONNECT WIRING TO AND REMOVE EXISTING STARTER ASSOCIATED WITH GAS BURNER SYSTEM BEING REMOVED.
- 3 DISCONNECT AND REMOVE WIRING TO EXISTING STARTER FOR CP-12. LABEL STARTER AS SPARE.

KEYNOTES (THIS DRAWING)


- RECONFIGURE MCC BUCKET 1C AND 1D TO ACCEPT NEMA SIZE 4 COMBINATION STARTER WITH 110A MOTOR CIRCUIT PROTECTOR FOR DIGESTER MIXING PUMP NO.1.
- RECONFIGURE MCC BUCKET 3A AND 3B TO ACCEPT NEMA SIZE 4 COMBINATION STARTER WITH 110A MOTOR CIRCUIT PROTECTOR FOR DIGESTER MIXING PUMP NO.2.
- $\overline{3}$ EXISTING 120V PANEL LP-B.
- 4 EXISTING MAIN CIRCUIT BREAKER. REPLACE EXISTING FEEDER CONDUCTORS. SEE DRAWING E-5 FOR DETAILS.
- PROVIDE 30A, 3 POLE BREAKER TO FEED DIGESTER CONTROL PANEL.



DIGESTER CONTROL PANEL INTERCONNECT DIAGRAM SCALE: NONE



DIGESTER BUILDING GAS DETECTION INTERCONNECT DIAGRAM SCALE: NONE



MCC-B ELEVATION

FLOOR —

, ILLINOIS DIGESTER

Y OF . SIDE

CITY ASTS

ENGINEERS
DESIGN FIRM REGISTRATION No. 184-000450 1817 SOUTH NEIL STREET SUITE 100 CHAMPAIGN, ILLINOIS (217) 373-8900 (217) 373-8923

DESIGNED BY: DRAWN BY: DRAWN BY: RSL
CHECKED BY: CEC/SEM DATE CHECKED: ____07/06 NOTE: DIMENSIONAL DATA IS NOT TO BE OBTAINED BY

THIS DRAWING.

SCALING ANY PORTION OF

J02570

PROJECT No.

DRAWING TITLE

DIGESTER BUILDING MCC-B ELEVATION AND DETAILS

E-16

Mon. 07 Aug 2006 - 4:38pm Last Edited By: CNL Drawing Name: P:\J02570\Joliot Easteide Studge\ELEC\E-16 (digester details).dug

BASEMENT ELECTRICAL DEMOLITION PLAN BASEMENT ELECTRICAL PROPOSED PLAN

ELECTRICAL NOTES (THIS DRAWING)

- 1. SEE DRAWING E-1 FOR GENERAL NOTES, SYMBOL LIST AND SUGGESTED SEQUENCE OF CONSTRUCTION.
- 2. SEE PROCESS MOTOR SCHEDULE ON DRAWING E-4 FOR ADDITIONAL INFORMATION ON MOTOR LOADS.

DEMOLITION KEYNOTES (THIS DRAWING)

DISCONNECT AND REMOVE EXISTING DISCONNECT SWITCH AND ASSOCIATED WIRING BACK TO MCC-A (SEE DRAWING E-18 FOR LOCATION). REMOVE EXISTING CONDUIT AND WIRE FROM DISCONNECT SWITCH TO THICKENED SLUDGE TRANSFER PUMP MOTOR. EXISTING CONDUIT UP TO MCC-A SHALL REMAIN AND BE REUSED.

KEYNOTES (THIS DRAWING)

- GRAVITY BELT THICKENER SLUDGE PUMP NO.3 (P-603). PROVIDE HEAVY DUTY, NEMA 12, NON-FUSIBLE, 100A, 3 POLE DISCONNECT SWITCH.
- GRAVITY BELT THICKENER SLUDGE PUMP NO.2 (P-602). PROVIDE HEAVY DUTY, NEMA 12, NON-FUSIBLE, 100A, 3 POLE DISCONNECT SWITCH.
- GRAVITY BELT THICKENER SLUDGE PUMP NO.1 (P-601). PROVIDE HEAVY DUTY, NEMA 12, NON-FUSIBLE, 100A, 3 POLE DISCONNECT SWITCH.
- START/STOP LOCAL CONTROL STATION FOR GRAVITY BELT THICKENER SLUDGE PUMP.

CITY OF JOLIET, ILLINOIS EASTSIDE WWTP DIGESTER IMPROVEMENTS



ENGINEERS

DESIGN FIRM REGISTRATION
No. 184-000450

1817 SOUTH NEIL STREET
SUITE 100
CHAMPAIGN, ILLINOIS
(217) 373-8900

(217) 373-8923

DESIGNED BY: JJF
DRAWN BY: RSL
CHECKED BY: CEC/SEM
DATE CHECKED: 07/06

NOTE: DIMENSIONAL DATA IS
NOT TO BE OBTAINED BY
SCALING ANY PORTION OF

THIS DRAWING.

TE REVISION

J02570


DRAWING TITLE


OLIDS PROCESSING JILDING BASEMENT ELECTRICAL PLANS

DRAWING No.

KEY PLAN
SOLIDS PROCESSING BUILDING
DRAWING 37 OF

m, 07 Aug 2006 — 4:38pm Last Edited By: CKL Drawing Name: P:\J02570\Joliet Easteide Studge\ELEC\E—17 (ealide processing).dwg





ENGINEERS
DESIGN FIRM REGISTRATION No. 184-000450 1817 SOUTH NEIL STREET

NOTE: DIMENSIONAL DATA IS NOT TO BE OBTAINED BY SCALING ANY PORTION OF

ELECTRICAL NOTES (THIS DRAWING)

1. SEE DRAWING E-1 FOR GENERAL NOTES, SYMBOL LIST AND SUGGESTED SEQUENCE OF CONSTRUCTION.

CITY OF JOLIET, ILLINOIS EASTSIDE WWTP DIGESTER IMPROVEMENTS

Clark Dietz

ENGINEERS

DESIGN FIRM REGISTRATION
NO. 184-000450

1817 SOUTH NEIL STREET
SUITE 100
CHAMPAIGN, ILLINOIS
(217) 373-8900
(217) 373-8923

DESIGNED BY:

DRAWN BY:

CHECKED BY:

DATE CHECKED:

RSL

CEC/SEM

07/06

NOTE: DIMENSIONAL DATA IS NOT TO BE OBTAINED BY SCALING ANY PORTION OF THIS DRAWING.

DATE REVISION

PROJECT No.

J02570

DRAWING TITLE

DUCTBANK CABLE SCHEDULE										
MARK	FROM	ТО	WIRE							
Α	PMG-2	FEEDER BAY ON EXISTING PMG-1	3#2/0 (5KV)							
В	BLOWER BUILDING	CONTROL BUILDING	EXISTING CONTROL WIRING							
С	MSWB-1	EXISTING MCC-C	3#350, 1#3 GRD (480V)							
D	EXISTING I-LINE PANELBOARD	EXISTING MCC-B	REMOVE EXISTING 3#350 (480V)							
Е	PMG-2	EXISTING TRANSFORMER T-3	3#6 (5KV)							
F	EXISTING LV MANHOLE MH3	EXISTING MCC-E	EXISTING CONTROL WIRING							
G	EXISTING LV MANHOLE MH3	EXISTING MCC-E	EXISTING SIGNAL WIRING							
Н	EXISTING I-LINE PANELBOARD	EXISTING MCC-E	REMOVE EXISTING 6#350 (480V)							
J	MSWB-1	EXISTING MCC-B	3#600, 1#3 GRD (480V)							
K	EXISTING LV MANHOLE MH3	EXISTING MCC-B	EXISTING CONTROL WIRING							
L	EXISTING LV MANHOLE MH3	EXISTING MCC-B	EXISTING SIGNAL WIRING							
М	EXISTING HANDHOLE HH1	SOLIDS PROCESSING BUILDING	EXISTING CONTROL WIRING							
Ν	EXISTING HADNHOLE HH1	SOLIDS PROCESSING BUILDING	EXISTING SIGNAL WIRING							
0	EXISTING PMG-2	EXISTING PMG-1	REMOVE EXISTING 5KV CABLES							
Р	MSWB-1	EXISTING MCC-E	3#350, 1#2 GRD (480V)							
Q	MSWB-1	EXISTING C.B. ENGINE ROOM PANEL	3#350, 1#1 GRD (480V)							
R	EXISTING I-LINE PANELBOARD	EXISTING MCC-C	REMOVE EXISTING 3#500 (480V)							
S	(4) PRIMARY TANK GEAR DRIVE MOTORS	EXISTING MCC-E	12#10, 4#10G (480V)							
T	(4) PRIMARY TANK GEAR DRIVE MOTORS	EXISTING MCC-E	40#14 (20 SPARE), 4#14G (CONTRO							

1. ALL CONDUIT IN DUCTBANK SHALL BE PVC, EXCEPT FOR THE FIRST TEN FEET OF CONDUIT LEAVING A BUILDING,

STRUCTURE, MANHOLE, OR HANDHOLE WHICH SHALL BE RGS, UNLESS OTHERWISE NOTED.

2. ALL CABLES SHALL BE NEW FROM POINT TO POINT UNLESS INDICATED AS EXISTING WIRING.

—EXISTING CONCRETE ENCASED DUCTBANK -EXISTING CONCRETE ENCASED DUCTBANK -EXISTING CONCRETE ENCASED DUCTBANK —CONCRETE ENCASED DUCTBANK — SPARE 4) (4) SECTION D SECTION A SECTION B SECTION C EXISTING CONCRETE ENCASED DUCTBANK ENCASED DUCTBANK EXISTING CONCRETE ENCASED DUCTBANK CONCRETE ENCASED DUCTBANK — SPARE — SPARE 4 2 4 SECTION E SECTION F SECTION G SECTION H —CONCRETE ENCASED ENCASED DUCTBANK DUCTBANK CONCRETE ENCASED SPARE DUCTBANK -EXISTING CONCRETE ENCASED DUCTBANK (480V POWER) – SPARE (120V CONTROL) SECTION J SECTION K SECTION L SECTION M

DUCTBANK SECTIONS
SCALE: NONE

E-20

DIMENSIONS


LEN	NGTH	WIDTH	HEIGHT
	IN.	IN.	IN.
INSIDE	48	48	48
OUTSIDE	57	57	57 1/2
MIN. EXCAVATION HOLE SIZE	63	63	

	THICKNESS		WEIGHT
	IN.		LBS.
WALL	3 3/4	TOP	2,597
BEAM	NONE	BOTTOM	<u>2,974</u>
ROOF	5	TOTAL	5,571
FLOOR	4 1/2		

NOTES:

1. HANDHOLE AND HANDHOLE ACCESSORIES SHALL BE FURNISHED AND INSTALLED BY CONTRACTOR.

HANDHOLE DETAIL SCALE: NONE




SECTION R-R

ELECTRICAL NOTES (THIS DRAWING)


SEE DRAWING E-1 FOR GENERAL NOTES, SYMBOL LIST AND SUGGESTED SEQUENCE OF CONSTRUCTION.

ELECTRICAL EQUIPMENT PAD NOTES

- 1. PAD TO BE INSTALLED ON 12" COMPACTED CRUSHED ROCK BASE. INSTALL REINFORCING BARS.
- 2. EXACT LOCATIONS OF CONDUIT STUBS MAY VARY, COORDINATE EXACT LOCATIONS PRIOR TO CONSTRUCTION.
- 3. CONTRACTOR SHALL VERIFY ALL DIMENSIONS WITH PROVIDED EQUIPMENT.
- 4. CONCRETE PAD SHALL EXTEND 4" PAST EDGE OF ELECTRICAL EQUIPMENT.




GROUNDING ELECTRODE CONDUCTOR TRENCH DETAIL



PAD MOUNTED ELECTRICAL EQUIPMENT DETAIL - PLAN VIEW





PIPE BOLLARD DETAIL SCALE: NONE

r, illinois P digester Ients Y OF JOLIET, I TSIDE WWTP [IMPROVEME]

CITA

ENGINEERS
DESIGN FIRM REGISTRATION No. 184-000450 1817 SOUTH NEIL STREET SUITE 100 CHAMPAIGN, ILLINOIS (217) 373-8900 (217) 373-8923

DESIGNED BY: DRAWN BY: CHECKED BY: CEC/SEM DATE CHECKED: 07/06 NOTE: DIMENSIONAL DATA IS NOT TO BE OBTAINED BY SCALING ANY PORTION OF THIS DRAWING.

J02570 DRAWING TITLE

PROJECT No.

E-21