# CITY OF JOLIET WILL COUNTY, ILLINOIS SPECIFICATIONS, PLANS, CONTRACT PROPOSAL, CONTRACT AND CONTRACT BOND

## FOR THE PURCHASE OF UTILITIES DIVISION TWO (2) HEAVY DUTY TANDEM AXLE CAB / CHASIS 6X4 DUMP BODY AND ACCESSORIES

**CONTRACT NO. 2454-1219** 

APPROVED DEPARTMENT OF PUBLIC UTILITIES  Muon Sosle	SUBMITTED BY
DIRECTOR OF PUBLIC UTILITIES	CONTRACTORS NAME
DATE: November 7, 2019	ADDRESS
APPROVED	CITY AND STATE
DEPARTMENT OF PUBLIC UTILITIES	
William & Both	PHONE
FIELD OPERATIONS SUPERINTENDENT	
DATE: November 7, 2019	DATE:, 2019

#### MANAGEMENT & BUDGET PURCHASING DIVISION 815/724-3925 815/724-3929 FAX



#### Prospective Bidder:

Enclosed are bid documents which may be of interest to your company.

Please note the date as to when these bids will be opened.

THIS BID DOCUMENT MUST BE RETURNED INTACT (THE SAME ORDER AS RECEIVED). FAILURE TO DO SO MAY INVALIDATE YOUR PROPOSAL.

ALL BIDS SHALL BE SUBMITTED IN AN OPAQUE, SEALED ENVELOPE TO THE CITY CLERK, 150 WEST JEFFERSON STREET, JOLIET, ILLINOIS 60432, PRIOR TO THE TIME AND DATE SET FORTH FOR BID OPENING IN THE NOTICE TO BIDDERS. EACH BID SHALL BE ADDRESSED TO THE CITY CLERK AND SHALL BEAR ON THE FACE OF THE ENVELOPE THE NAME OF THE BIDDER, AND A STATEMENT THAT IT IS A SEALED BID, TO BE OPENED FOR THE CONTRACT CONSIDERED, AT THE DATE AND HOUR SET FORTH IN THE INVITATION TO BID.

THE BIDDER SHALL ALSO STATE ON THE ENVELOPE THAT HE/SHE IS IN RECEIPT OF ALL ADDENDUMS TO THE CONTRACT.

ANY QUESTIONS OR CLARIFICATIONS CONCERNING THESE SPECIFICATIONS SHOULD BE DIRECTED TO MARGARET E. MCEVILLY, CONTRACT ADMINISTRATOR, PHONE NO. (815) 724-3925 OR (815) 724-3929 FAX.

ANY ORAL OR WRITTEN COMMENTS RECEIVED FROM ANY OTHER PERSON OTHER THAN THE CONTRACT ADMINISTRATOR, WILL NOT BE CONSIDERED AND ALSO, MAY INVALIDATE YOUR PROPOSAL.

THANK YOU FOR BIDDING.

MAYOR INTERIM CITY MANAGER

Bob O'Dekirk Steve Jones

COUNCILPERSONS CONTRACT ADMINISTRATOR

Margaret E. McEvilly

Don Dickinson
Larry E. Hug
Pat Mudron
Sherri Reardon
Bettye Gavin
Terry Morris
Jan Hallums Quillman
Michael F. Turk

#### **CONTRACT DOCUMENTS**

PROJECT: PURCHASE OF UTILITIES DIVISION TWO (2) HEAVY DUTY

TANDEM AXLE CAB / CHASIS 6X4 WITH DUMP BODY AND

**ACCESSORIES** 

DEPARTMENT: PUBLIC UTILTIES

**CITY OF JOLIET, ILLINOIS** 

CONTRACT NO. **2454-1219** 

STEVE JONES

INTERIM CITY MANAGER

MARGARET E. McEVILLY CONTRACT ADMINISTRATOR

#### LEGAL NOTICE CITY OF JOLIET ADVERTISEMENT TO BIDS

## PURCHASE OF UTILITIES DIVISION TWO (2) HEAVY DUTY TANDEM AXLE CAB / CHASIS 6X4 WITH DUMP BODY AND ACCESSORIES CONTRACT NO. 2454-1219

The City of Joliet, Illinois, does hereby invite sealed bids for the purchase of two (2) Heavy Duty Tandem Axle Cabs / Chassis 6x4 with Dump Body and Accessories for the Utilities Division.

Bids will be received at the Office of the City Clerk, City of Joliet Municipal Building, 150 West Jefferson Street, Joliet, Illinois 60432-4156 until 10:10 A.M. local time on Wednesday – December 4, 2019 at which time they will be opened and publicly read aloud.

Receipt of your document in any location other than City Clerk's office at City Hall, 150 W. Jefferson St., Joliet, IL 60432, does not constitute receipt. If you are using a delivery service, the fact that it was signed for by someone at City of Joliet does not constitute receipt. To ensure that your package was received prior to the opening, you can email cityclerk@joliet.gov or call 815-724-3780 to verify receipt of document.

Those desiring to bid may examine the bid documents and detailed specifications in the City of Joliet Purchasing Division, 150 W. Jefferson St., Joliet, IL 60432 between the hours of 8:00 A.M. and 4:30 P.M., Monday through Friday. Electronic copies can be downloaded free of charge at <a href="https://www.joliet.gov/departments/finance/purchasing/bids-proposals">https://www.joliet.gov/departments/finance/purchasing/bids-proposals</a>. No hard copies will be available for purchase.

Bidding Document holders should RSS ΑII sign up for feeds at https://www.ioliet.gov/departments/finance/purchasing/bids-proposals/purchase-of-vehicles and provide your first and last name and email address to automatically receive Addendums will also be posted on the City of Joliet's website at addendums. https://www.joliet.gov/departments/finance/purchasing/bids-proposals. The potential vendor/ contractor remains responsible for obtaining all addenda to the original specification so they should check the specific bid page before submitting a bid to make sure they have received all addendums to a specific contract. The City of Joliet's local qualified bidder ordinance does apply to this contract.

The City of Joliet reserves the right to reject any and all bids, parts of any and all bids, or to waive technical errors or omissions in bids.

The Contract shall be subject to the provisions of the *Prevailing Wage Act* (820 ILCS 130/1 et seq.) to the extent required by law and the City of Joliet Procurement Code (Section 2-430 – 2-453 of the Code of Ordinances.

Published in the Labor Record

Thursday – November 14, 2019

Steve Jones Interim City Manager

Margaret E. McEvilly Purchasing/Contracts Administrator This contract is eligible for the local bidder preference ordinance.

If you have read all of the documentation, filled out the form found online at

http://www.joliet.gov/departments/finance/purchasing/prequalificat ion-process, have been prequalified by the City of Joliet as a Local Bidder and wish to be qualified as a local bidder for this contract, please sign this sheet.

VENDOR NAME		
VENDOR ADDRESS		
CITY, STREET, ZIP		
CONTACT PERSON		
SIGNATURE		
PHONE		
EMAIL ADDRESS		

Complete this form ONLY if you submitted the CITY OF JOLIET LOCAL BIDDER APPLICATION FORM from the above website AND have been approved as a local bidder.

If you have questions about this form, please call Purchasing/Contracts Administrator Margaret McEvilly at 815-724-3926.

#### CITY OF JOLIET

#### 150 WEST JEFFERSON STREET

**JOLIET, ILLINOIS 60432-4158** 

CONTRACT DOCUMENTS FOR: PURCHASE OF UTILITIES DIVISION TWO (2)

**HEAVY DUTY TANDEM AXLE CAB / CHASIS 6X4** 

WITH DUMP BODY AND ACCESSORIES

User Department: PUBLIC UTILITIES

Date and Time of Bid Opening: **DECEMBER 4, 2019 @ 10:10 A.M.** 

Bid Security: NONE

Performance Security: NONE

Prequalification Necessary: NONE

Insurance: NONE

Bob O'Dekirk Steve Jones

Mayor Interim City Manager

Margaret E. McEvilly
Contract Administrator

**Council Members:** 

Don Dickinson
Larry E. Hug
Pat Mudron
Sherri Reardon
Bettye Gavin
Terry Morris
Jan Hallums Quillman
Michael F. Turk

#### **INSTRUCTION TO BIDDERS**

### PROJECT: PURCHASE OF UTILITIES DIVISION TWO (2) HEAVY DUTY TANDEM AXLE CAB / CHASIS 6X4 WITH DUMP BODY AND ACCESSORIES

NOTE: BY SUBMITTING A BID, THE BIDDER WARRANTS THAT HE HAS FAMILIARIZED HIMSELF WITH ALL REQUIREMENTS OF THE CONTRACT DOCUMENTS AS WELL AS THE CITY OF JOLIET PURCHASING ORDINANCE.

#### **DEFINITIONS**:

The following definitions shall apply wherever they appear in the contract documents.

CITY: CITY OF JOLIET

OWNER: THE CITY OF JOLIET

BID: THE OFFER OF THE BIDDER

BIDDER: ANY INDIVIDUAL, CORPORATION OR PARTNERSHIP

WHO SUBMITS A BID.

CONTRACT DOCUMENTS - Invitation to Bid Instructions, General Conditions, Special Provisions, Specifications, Drawings, Addendums, Proposal (in so far as it is not inconsistent with other contract documents) and Contract Form.

Other definitions shall be as defined in City of Joliet Ordinance 7345 or in other Contract Documents.

#### 1. BIDS - GENERAL

Bids shall be made in accordance with the instructions. Failure to execute proposals as required may, in the discretion of the City, be cause for rejection of the bid.

#### 2. FORMS

Bids shall be submitted on the forms provided by the City of Joliet. Each bid must be submitted bound with all other contract documents.

#### 3. BLANKS; CORRECTIONS

All blank spaces on any contract document shall be filled in with typewritten figures or ink. Any erasures or corrections shall be dated and initialed by the bidder.

#### 4. **SUBMISSION**

Bids shall be submitted in opaque sealed envelopes to the City Clerk, 150 West Jefferson Street, Joliet, Illinois 60432-4156, prior to the time and date set forth for bid opening in the Notice to Bidders. Each bid shall be addressed to the City Clerk and shall bear on the face of the envelope the name of the bidder, and a statement that it is a sealed bid to be opened for the contract at the date and hour as set forth in the invitation to bid.

#### 5. **EXECUTION**

Proposals shall be signed by the bidder. If the bidder is a corporation, the proposal shall bear the name of the corporation, signed by an officer authorized to bind the corporation, and sealed with the corporate seal.

#### 6. WITHDRAWAL

Bids may be withdrawn previous to the time of the bid opening by written request. However, no bid shall be withdrawn within the thirty (30) day period after the time set for bid opening. Bidders withdrawing their bids prior to the time and date set for bid opening may still submit another bid if done in accordance with these instructions.

#### 7. WORDS AND FIGURES

Where amounts are given in both words and figures, the words will govern.

#### 8. <u>UNIT PRICE</u>

When unit prices are called for, bids shall include all unit cost items and alternatives shown on the proposal. When an error is made in extending total prices, the unit price will govern.

#### 9. TAXES

All bids shall include all applicable taxes. The State of Illinois Sales Tax and Federal Excise Taxes are not applicable to sales made in the City.

#### 10. <u>NET PRICE</u>

Bid prices shall be net, including therein transportation and handling charges F.O.B. City of Joliet, and shall further include all charges of whatsoever sort for labor and materials contained in the work or materials designated in the specifications and proposals.

#### 11. BID SECURITY

#### 12. <u>BID SECURITY RETURN</u>

#### 13. <u>INTERPRETATIONS</u>

Interpretations of the meaning of any item in the Contract Documents shall be valid only if issued in writing by the Owner or the Owner's representative designated in the Contract Documents.

#### 14. FAMILIARITY WITH CONTRACT DOCUMENTS AND SITE

Bidders shall examine all contract documents including General Conditions and Specifications, inspect and acquaint himself fully with site conditions (surface and subsurface), working conditions and restraints, if applicable, prior to the submission of his bid.

#### 15. <u>ALTERNATE EQUIPMENT OR MATERIALS</u>

- a. Bids shall be evaluated and considered on equipment and/or materials complying substantially with the contract specifications. If any bidder deviates from the contract specifications or provides a substitute for any required equipment and/or material listed in the contract specifications, that bidder shall list such deviations and/or substitutions, including technical data when applicable, in a letter attached to the bid or on a form that may be provided by the City with the bid documents.
- b. Brand names, which may be mentioned in the contract specifications, are used only as a reference to the type and quality of equipment and/or materials desired. However, any deviation from or substitution in a brand name stated in the contract specifications shall be listed as required under paragraph (a) of this section.
- c. The City reserves the right to determine whether any deviations and substitutions listed by the bidder are within the intent of the contract specifications and will reasonably meet the service requirements of the using department.
- d. A bidder's failure to list any deviations from or substitutions in the contract specifications as required under paragraph (a) of this section may result in the rejection of the bid.

#### 16. <u>DESCRIPTIVE LITERATURE:</u> <u>EQUIPMENT OR MATERIALS</u>

Each bidder bidding on contracts to furnish equipment or materials shall furnish with his proposal two (2) copies of descriptive literature on the supplies or equipment being bid and manufacturer's specifications shall be in sufficient detail to permit proper evaluation of the bid.

#### 17. RESPONSIBILITY OF BIDDERS

No contract will be awarded to any person, firm, or corporation that is in arrears to the City of Joliet, Illinois upon any debt or contract, or who has failed to execute in whole or in part, in a satisfactory manner, any contract with the City of Joliet, or who is a defaulter as to surety or otherwise upon any obligation to the City of Joliet, Illinois.

#### 18. CITY'S RIGHT TO ACCEPT OR REJECT

The City of Joliet reserves the right to accept any bid which may be deemed to be in the best interest of the City of Joliet. The City of Joliet further reserves the right to reject any or all bids.

#### 19. AWARDING OF CONTRACT

The Contract shall be awarded to the lowest responsible bidder based on criteria as set forth in the City of Joliet Purchasing Ordinance.

#### 20. <u>ALTERNATE AND MULTIPLE BIDS</u>

Unless otherwise indicated in these bid documents, the Contractor may not submit alternate or multiple bids as part of this bid package. The submission of more than one bid within a single bid package may be cause for rejection of any or all of the bids of that contractor.

#### 21. AFFIDAVITS

The Affidavits included in these Contract Documents must be executed and submitted with the bid.

### MANAGEMENT & BUDGET PURCHASING DIVISION

150 W. Jefferson Street Joliet, IL 60432 (815) 724-3925 (815) 724-3929 (fax)



#### **CITY OF JOLIET**

#### **NOTICE**

The City of Joliet has adopted the Responsible Bidder Ordinance. In addition to any other requirement, unless otherwise expressly stated in a bid solicitation or an award of contract, all bidders must comply with the following requirements in order to submit a bid or be awarded a contract and include satisfactory evidence thereof in its bid.

- (1) The bidder must be a duly organized legal entity in good standing with the Illinois Secretary of State and in compliance with all laws prerequisite to doing business in Illinois.
- (2) The bidder must have a valid Federal Employer Tax Identification Number or Social Security Number.
- (3) The bidder must be an equal opportunity employer and comply with Section 2000(e) of Chapter 21, Title 42 of the United States Code and Executive Order No. 11246.
- (4) The bidder shall provide certificates of insurance indicating the following coverages if called for in the bid solicitation: general liability, workers compensation, completed operations, automobile, hazardous occupation and product liability.
- (5) The bidder must comply with all provisions of the Illinois Prevailing Wage Act (820 ILCS 130), including wages, medical and hospitalization insurance and retirement for those trades covered in the Act.
- (6) All contractors and sub-contractors performing services covered by the Illinois Prevailing Wage Act must submit to the City the certified payrolls required by the Act, as amended by Illinois Public Act 94-0515.
- (7) For construction projects (construction of new facilities, renovation of existing facilities or road construction projects) over \$25,000.00, or demolition contracts over \$25,000.00, the bidder must provide apprenticeship and training programs that are either registered with the United States Department of Labor's Bureau of Apprenticeship and Training or are reasonably equivalent to such programs.

MARGARET E. MCEVILLY
Purchasing/Contract Administrator

### NOTICE TO BIDDERS – ETHICS ORDINANCE AND INSPECTOR GENERAL COMPLIANCE

The City of Joliet has an Ethics Ordinance (Section 2-333 et seq. of the Code of Ordinances of the City of Joliet) which prohibits any appointed or elected official of the City of Joliet, or any employee of the City of Joliet from receiving or soliciting anything of value to influence that City official or employee in carrying out his or her official duties. The City of Joliet appreciates your anticipated cooperation in refraining from offering any official or employee anything, item, service, or favor of value to influence that person's decision on any City business. With your cooperation, the City of Joliet will achieve its goal of maintaining a fair and competitive contract procedure that promotes the best interests of the citizens of the City of Joliet. You should report immediately any violation of the Ethics Ordinance to the Inspector General, including any solicitation of a thing of value by a City official or employee. A bidder or contractor's participation or encouragement in the violation of the Ethics Ordinance may result in the rejection of a bid, termination of contract, or declaration of ineligibility to bid on future contracts.

It is the duty of any bidder, proposer, consultant, subcontractor, applicant for prequalification for a City contract, applicant for local bidder certification, and all officers, directors, agents, partners and employees of any bidder, proposer, consultant, subcontractor, or such applicant to cooperate with the Inspector General in any investigation or hearing undertaken pursuant to City of Joliet Ordinance 2-180, et. seq.. Any of the aforementioned parties understands and will abide by all provisions of the aforementioned Ordinance. All contractors must inform subcontractors of the provision and require understanding and compliance with it.

A copy of the City of Joliet Ethics Ordinance and all other City Ordinances are available in the City Clerk's office or on the City website for your review.

### **GENERAL CONDITIONS**

Please see the City of Joliet Special Provision and General Conditions Booklet Adopted February 29, 2016 available on Joliet.gov.

#### **CITY OF JOLIET**

#### 2019 SPECIFICATION FOR

## UTILITIES DIVISION TWO (2) HEAVY DUTY TANDEM AXLE CAB/CHASSIS 6X4 WITH DUMP BODY & ACCESSORIES

#### **PURPOSE:**

The intent of these specifications is to set forth minimum requirements for the purchase of two (2) new 2020; three axle truck chassis and related equipment by the City of Joliet for use by the Department of Utilities.

#### SCOPE:

This unit will be used for hauling of materials including but not limited to stone (gravel) hot asphalt and dirt. Use will be on local roadways from quarries to landfills, spreading and dumping of loads at work sites.

#### **SPECIAL PROVISIONS**

- All bids shall be in strict accordance with all provisions contained herein and shall comply with the specifications attached hereto
- Bids shall be submitted on the printed forms provided for that purpose and bound herewith and must be signed
- Bid forms shall be completed in full not be detached from this binding
- The complete set of proposal documents shall be submitted with the proposal
- Bidders shall answer each compliance question on the specifications by marking either the YES or the NO blank
- Exceptions shall be explained in detail on a separate page
- If all blanks are marked YES, exact compliance is required

- The board reserves the right to reject any or all bids or to accept any bid which may be deemed to be in the best interest of the City of Joliet
- No bid shall be withdrawn within thirty (30) days after the scheduled time for the opening of the bids
- Bidders must submit a firm bid
- A bidder shall not stipulate in his proposal any condition not contained in the proposal documents
- Any qualifying statements or conditions may be considered irregular and as not being responsive to the Advertisement for Bids
- Each bidder shall furnish with his proposal two copies of descriptive literature on the
  equipment being bid and the manufacturer's specifications in complete detail. Said
  brochure and manufacturer's specifications shall be sufficiently detailed to permit proper
  evaluation of bid
- When delivered the truck shall be complete in all parts and ready for immediate use
- The manufacturer shall warranty the truck and equipment installer shall warranty the equipment against defective materials and workmanship per specifications
- A statement providing the period of warranty coverage in both mileage/hours and in calendar time shall be provided and shall state any exclusions of units/parts
- Any item not specifically excluded in this statement shall be fully covered by the warranty
- Any defects shall be promptly corrected without cost to the City of Joliet
- No charges will be allowed for taxes. The City of Joliet is exempt from all Federal, State and Local taxes
- Two complete sets of shop manuals shall be provided upon delivery of each truck. Such manuals shall cover the truck chassis and all equipment installed thereon. Failure to provide these manuals at the time of delivery may subject the completed unit to rejection as incomplete and further may delay payment of the invoice
- The completed unit shall be equipped with the manufacture's equipment and accessories which are included as standard in the published literature for the unit. No such item of equipment or accessory shall be removed or omitted for the reason that it

was not specified. Standard product items may be removed only where it is necessary to install other items in lieu thereof in order to comply with these specifications

- The ultimate quantity of units purchased shall be at the option of the City of Joliet
- All articles provided shall be new, unused and of current design and production
- All submitted bids must include pricing for the purchase of one unit and any discount pricing for the purchase of two units
- Questions regarding technical items contained in these specifications should be directed to:

Mr. David Druzik City of Joliet Superintendent of Fleet Services 402 N. Chicago St. Joliet, IL 60432 (815) 724-4300

• Fleet standardization. It is expressly understood that unless a situation stating NO EXCEPTION is made for a given article, that a substitution of like kind and quality may be made. It is the intent of the City to fully standardize this dump body and hoist, therefore these articles are subject to the NO EXCEPTION stipulation

## BID SPECIFICIATIONS FOR HEAVY DUTY TANDEM AXLE CHASIS 6X4 WITH DUMP BODY & ACCESSORIES

TYPE:		
Current model year 2019/2020 Tandem axle cab and chassis	YES	NO
62,540 GVWR, conventional cab, 195" minimum wheel base		
with 128" cab to trunnion, set back front axle		
ENGINE:		
Cummins L9 minimum 330 HP @ 2000 RPM minimum	YES	NO
1,000 FT/LB torque @1,400 RPM 2,200 RPM governed speed		
EPA certified for 2018 emissions with SCR technology. Turbo		
charged and after cooled. Stainless steel oil pan with minimum		
24-quart capacity. Heavy duty dual element air cleaner with resi	triction ind	dicator.
ENGINE WARRANTY:		
Minimum 60 months 6,000 hours 100% parts and labor on any	YES	NO
internally lubricated part of the engine including turbo charger a	nd	
fuel transfer pump. All harnesses and connectors of the engine		
control system, IDM, ECM, fuel injectors. Warranty to begin on	the	
date that the completed vehicle is accepted and put into service		
by the Joliet Fleet Services.		

CT	RICAL:		
A.	Heavy duty 12-volt 160-amp alternator.	YES	NO_
В.	3 – maintenance free 12-volt batteries. 1950 CCA	YES	NO_
	minimum with remote mounted jump start stud.		
C.	Batteries mounted in a steel battery box with	YES	NO_
	fiberglass cover.		
D.	All engine compartment wiring must be encased in	YES	NO_
	convoluted tubing and all chassis wiring in frame rails		
	must be encased in jacketed cable.		
Ε.	Manual reset circuit breakers shall replace all fuses in	YES	NO_
	circuits rated for more than 5 amps. Breakers shall be		
	type III with trip indicators.		
F.	Type 2 terminal post mounted in Cab with a power	YES	NO_
	distribution center for uses as an all circuit power source.		
G.	2 cigar lighter plugs with a separate auxiliary dash	YES	NO_
	mounted cigar type power receptacle.		
Н.	2 USB charging receptacles	YES	NO_
I.	Body builder wiring to rear of frame with stop/tail/turn	YES	NO_
	and marker light circuits, ignition controlled auxiliary feed.		
	Groundless trailer socket.		
	SMISSION:		
	A. Allison RDS close ratio 6-speed automatic transmission	YES	NO_
	with push button shift control.		
	B Left and right side PTO Provision Less Retarder	VFS	NO

	C. Allison WT with spare input/output.	YES	NO
	D. Integral mechanical lockup	YES	NO
	E. External cooler and filter.	YES	NO
	F. Transmission ECM mounted inside cab	YES	NO
<u>TRANS</u>	SMISSION WARRANTY:		
Minim	um 2-year unlimited mileage.	YES	NO
COOLI	NG SYSTEM:		
A.	Heavy duty radiator and cooling system with integral	YES	NO
	coolant conditioner and spin on coolant filter element.		
В.	Engine equipped Horton Drive-Master nylon cooling	YES	NO
	fan with automatic on/off control.		
C.	Radiator will include transmission cooler.	YES	NO
D.	Radiator and heater hoses shall be silicone, molded type	YES	NO
E.	Hose clamps shall be constant torque for all hoses	YES	NO
	over 1.0" diameter.		
F.	120 volt/1250 watt engine block heather with connector	YES	NO
	socket mounted below driver's door.		
<u>EXHAU</u>	<u>UST:</u>		
A.	Muffler and after treatment device RH under cab with shielding.	YES	NO

В.	Vertical bright finish tailpipe, tailpipe guard and frame	YES	NO
	mounted on right side with under cab muffler. Vertical		
	muffler not acceptable.		
C.	Turn back type tail pipe for single exhaust.	YES	NO
D.	Stainless steel flex pipe.	YES	NO
Ε.	Exhaust height of 10' 11"	YES	NO
FRON'	T AXLE:		
A.	Meritor MFS 20 20,000 LB front axle.	YES	NO
В.	Greaseable, sealed bronze king pin bushings.	YES	NO
C.	Equipped with Stemco oil seals and synthetic lube.	YES	NO
D.	Equipped with parabolic tapered leaf springs with	YES	NO
	20,000 LB capacity.		
E.	Heavy duty shock absorbers.	YES	NO
F.	Sheppard M-100/M-80 dual power steering.	YES	NO
REAR .	AXLE:		
A.	Dana Spicer D46-170 rear axle single reduction 46,000 lb.	YES	NO
	capacity with no spin locking differential.		
В.	Reduction shall render governed top speed of 60 miles	YES	NO
	per hour maximum.		
C.	Power divider lock out and electric over air operated cab	YES	NO
	control with indicator light.		

	walking beam type 54" axle spacing 46,000 lb.		
	capacity with rubber springs, rubber end bushings		
	and transverse torque rods less shock absorbers.		
Ε.	Spring pins shall include maintenance free rubber bushing	gs <b>YES</b>	NO_
RIVE	LINE:		
A.	Spicer SAE1020 with nylon coated splines and quick YES	N	o
	service half round end yokes, 1710 HD main shaft		
	and 1610 inter-axle shaft.		
BRAKI	<u>ES:</u>		
	<u>ES:</u> Front brakes shall be 16.5 X 6-inch air cam actuated	YES	NO_
		YES	NO_
A.	Front brakes shall be 16.5 X 6-inch air cam actuated	YES	NO_
A.	Front brakes shall be 16.5 X 6-inch air cam actuated with 24 sq. in. long stroke brake chambers.		
A. B.	Front brakes shall be 16.5 X 6-inch air cam actuated with 24 sq. in. long stroke brake chambers.  Rear brakes shall be 16.5 X 7-inch air cam actuated with	YES	
A. B.	Front brakes shall be 16.5 X 6-inch air cam actuated with 24 sq. in. long stroke brake chambers.  Rear brakes shall be 16.5 X 7-inch air cam actuated with MGM TR 3030 long stroke brake chambers.	YES	NO_
В.	Front brakes shall be 16.5 X 6-inch air cam actuated with 24 sq. in. long stroke brake chambers.  Rear brakes shall be 16.5 X 7-inch air cam actuated with MGM TR 3030 long stroke brake chambers.  Rear brakes shall include spring actuated parking brake	YES	NO_
A. B.	Front brakes shall be 16.5 X 6-inch air cam actuated with 24 sq. in. long stroke brake chambers.  Rear brakes shall be 16.5 X 7-inch air cam actuated with MGM TR 3030 long stroke brake chambers.  Rear brakes shall include spring actuated parking brake to be activated by a color-coded yellow knob located on	YES	NO_
A. B.	Front brakes shall be 16.5 X 6-inch air cam actuated with 24 sq. in. long stroke brake chambers.  Rear brakes shall be 16.5 X 7-inch air cam actuated with MGM TR 3030 long stroke brake chambers.  Rear brakes shall include spring actuated parking brake to be activated by a color-coded yellow knob located on the instrument panel.	YES	NO_

#### **AIR SYSTEM:**

A.	Bendix Tu-Flo 550 series air compressor rated at 13.2 CFM	YES	NO
	or greater.		
В.	Full dual air with moisture ejected, auto heated Bendix	YES	NO
	AD-9 air dryer.		
C.	Bendix automatic drain valve model DV-2 with heater	YES	NO
D.	Spring brake modulation system.	YES	NO
		-	
FRAM	<u>E:</u>		
A.	Single heat-treated alloy steel frame rail (120,000 psi yield	)YES	NO
В.	Minimum dimension of 10.866" X 3.622" X 0.375.	YES	NO
C.	Minimum resisting bending moment 2,500,000.	YES	NO
D.	All fasteners flanged head grade 8.	YES	NO
E.	Two frame mounted front tow hooks.	YES	NO
F.	Powder coated argent steel swept back front bumper	YES	NO
TIRES/	<u>'WHEELS:</u>		
A.	(2) front tires #315/80 R 22.5 unisteel G291 Goodyear,	YES	NO
	482 REV/Mile, load range J.		
В.	Front disc 22.5" white powder coat painted steel, 10-stud,	YES	NO
	hub piloted, flanged nut, metric mount, 9.0 DC rims with		
	steel hubs.		
C.	(8) rear tires 12R/22.5 unisteel 16 ply G282MSDM+S	YES	NO
	Goodyear, 481 REV/Mile load range H.		

D.	Dual rear disc wheels 22.5 white powder coat painted	YES	NO
	steel, 10 stud, hub piloted, flanged nut, metric mount, 8.2	5	
	DC rims with steel hubs.		
E.	(1) front (1) rear spare tire and wheel with each vehicle	YES	NO
FUEL 7	TANK:		
A.	100 gallon "D" style aluminum top draw fuel tank.	YES	NO
В.	19" depth mounted under left side of cab.	YES	NO
C.	Stainless steel mounting straps with full width rubber	YES	NO
	gasket between strap and tank.		
D.	Nylon tubing fuel lines with snap on O ring quick connect	YES	NO
	fittings on both ends.		
E.	Factory installed heated primary and secondary fuel	YES	NO
	filters in line prior to injection pump.		
F.	Minimum DEF tank capacity 7 gallons.	YES	NO
CAB II	NTERIIOR:		
A.	Factory installed air ride cab.	YES	NO
В.	Instrument panel will consist of the following gauges:	YES	NO
	coolant temperature, engine oil pressure, hourmeter,		
	voltmeter, air pressure, tachometer, speedometer and		
	fuel level. Warning lights are supplementary to gauges.		
C.	Warning indicators with alarm for low engine oil pressure,	YES	NO
	high coolant temp, low coolant level and transmission		
	temperature gauge.		

D.	High output integral heater/air conditioner and defroster	YES	NO	
	with 3 speed blower fan.			
E.	Switches for heated mirrors should be located on the	YES	NO	
	instrument panel.			
F.	Filter minder air cleaner restriction gauge mounted in the	YES	NO	
	instrument panel.			
G.	Wiper switch including control for intermittent wiper	YES	NO	
	incorporated on the turn signal switch lever.			
Н.	AM/FM electronically tuned radio including capability	YES	NO	
	for NOAA weather broadcasts.			
I.	Automatic canceling heavy duty turn/hazard signal switch	YES	NO	
	with heavy duty flasher.			
J.	Sun visors driver and passenger sides.	YES	NO	
K.	Molded armrest located on each door.	YES	NO	
L.	Factory installed power windows.	YES	NO	
M.	Factory installed power door locks.	YES	NO	
N.	Custom type cab that includes sound deadening and	YES	NO	
	ventilation package with sound insulation for the dash			
	and engine cover.			
Ο.	Black rubber flooring.	YES	NO	
Ρ.	Dome light with door activated courtesy lights.	YES	NO	
Q.	Grab handles located on each A pillar	YES	NO	
R.	Overhead console with storage pockets with retainer nets	YES	NO	
S.	Factory installed dash mounted 6 pack rocker switches.	YES	NO	
	Switches are protected by factory circuit breaker and			
	terminate behind the left-hand seat in a power distribution	n		
	panel.			
т.	Tilt adjustable steering column.	YES	NO	
U.	Control for electric horns and electronic variable speed	YES	NO	
	throttle control mounted on steering wheel.			

٧.	Air suspended high back driver and passenger seats with	YES	NO
	integral headrests. Cloth covered isolated with 2 position		
	front cushion adjustment. 6 to 17-degree seat-back		
	adjustment with adjustable lumbar support.		
W.	Seats equipped with 3-point lap and shoulder belt.	YES	NO
Χ.	Seat air controls (National 2000 Model 295) located on	YES	NO
	side of seat to prevent accidental operation by occupant's	leg.	
Υ.	Total of 6 ignition and door keys.	YES	NO
	WEEDLAD.		
B E	XTERIOR:		
A.	Factory painted base coat/clear coat code #6894 Blue.	YES	NO
В.	Conventional style cab with tilting fiberglass hood	YES	NO
	assembly, stationary front grille with bug screen.		
C.	Injection molded TPO fender extensions.	YES	NO
D.	Dual electric 2-speed cowl mounted windshield wipers	YES	NO
	with intermittent feature.		
E.	Electric windshield wipers.	YES	NO
F.	Air solenoid operated single trumpet air horn mounted	YES	NO
	behind front bumper.		
G.	Dual powered 7.55" X 14.10" with 102" wide spacing	YES	NO
	rectangular mirrors with integral convex both sides with		
	heated heads, thermostatically controlled, LED clearance		
	lights with breakaway brackets.		
Н.	Safety tread steps with self-cleaning mud and snow grates	YES	NO
	at entry points on both driver and passenger side of cab.		
l.	Grip strut step located below the step recess under the	YES	NO
	fuel tank.		

K.	Parking lights with integral turn signals.	YES	NO	_
L.	Lexan lenses.	YES	NO	_
M.	Par 56 halogen sealed beam headlights.	YES	NO	_
N.	5 ICC marker and clearance lights.	YES	NO	_
Ο.	All glass to be tinted.	YES	NO	_
Р.	Splash guards installed to protect the battery box,	YES	NO	_
	steps fuel tank and air tanks.			
BODY:				
A.	Cross member less type dump body constructed	YES	NO	_
	of steel. Cross members are not acceptable.			
В.	Capacity shall be 11.5 to 14.1 cu yard.	YES	NO	_
C.	Inside length shall be 15'.	YES	NO	_
D.	Inside width shall be 84" at front.	YES	NO	_
E.	Side height shall be 36".	YES	NO	_
F.	Tailgate height shall be 44".	YES	NO	_
G.	Head sheet height shall be 58".	YES	NO	_
Н.	One piece 7-gauge steel strength sides and head sheet.	YES	NO	_
I.	Seamless fully boxed top rail, horizontal side brace and	YES	NO	_
	bottom rub rail shall be sloping (dirt shedding).			
J.	One piece tapered front corner post with 4" side	YES	NO	_
	board pocket.			
K.	7-gauge full depth rear corner post tied to an 8" structure	al <b>YES</b> _	NO	_
	channel rear apron. Joint further reinforced with a ¼" pla	ate		
	to prevent flexing. Dog house formed in and extend to a			
	maximum of 13" into the load area.			
L.	Entire body continuously welded. Skip welds with caulk	YES	NO	_

filler between welds will not be accepted.

M.	$\frac{1}{2}$ X 1 $\frac{1}{2}$ flat steel bar tarp/step rails located at the top of	YES	_NO
	the rub rail slope and top of center brace slope.		
N.	Must be fastened longitudinally and be flush with the	YES	_NO
	outside of the rails to serve as a walk rail and a tarp tie rail		
Ο.	The bar on both the street and curb side will be welded at	YES	_NO
	the front and rear corner posts of the dump body with star	nd	
	offs placed between the bar and the body side equally		
	spaced no more than 36" apart.		
Ρ.	The standoffs will be the same material as the bar and	YES	_NO
	welded to the body side and bar.		
Q.	A steel folding ladder will be welded to the front left	YES	_NO
	corner of the dump body.		
R.	The floor shall run full length and be one-piece ¼ AR	YES	_NO
	400 steel continuously welded 2" wide floor to side radius.		
S.	Long sills shall be one piece 8" X 13.0 lb. I beam	YES	_NO
т.	Mounting height shall not exceed 9".	YES	_NO
U.	Tailgate will be one piece of 7-gauge steel with a minimum	YES	_NO
	of two horizontal braces and lifting D ring for removal.		
٧.	Fully boxed perimeter with all horizontal surfaces sloped	YES	_NO
	outward (dirt shedding).		
W.	½" minimum flame cut numbering upper pivots with no	YES	_NO
	fewer than two per side.		
Χ.	1" minimum flame cut offset type upper hinge plates.	YES	_NO
Υ.	¾" minimum lower latch plates with no fewer than	YES	_NO
	two per side.		
Z.	1 ¼" minimum upper and lower steel pins	YES	_NO
<b>4</b> A.	All above hardware shall be steel.	YES	_NO
3B.	Standard type 24 air brake chamber with a spring over	YES	_NO
	center latch air trip tailgate release to prevent accidental		
	release of tailgate in the event of a loss of air pressure.		

CC.	Stainless steel busnings on all pivot points to reduce	YES	_NO
	seizing with grease zerks.		
DD	. Manual push-pull type air cab control valve.	YES	_NO
EE.	Lines running from cab to air chamber to be protected		
	by loom and carefully secured to prevent damage by		
	mechanical forces or heat.		
FF.	Formed 10-gauge steel cab shield attached to front of the	YES	_NO
	body by continuous weld on top, sides and bottom to prev	rent	
	rust and staining of the front body.		
GG.	Cab shield shall extend forward from the body a distance	YES	_NO
	of 22" and clear the cab roof by 2" min and 4" max.		
нн.	Support gussets shall form the sides of the cab shield	YES	_NO
	and be continuously welded.		
II.	8-gauge steel sloping side boards matching the horizontal	YES	_NO
	top and bottom rails of the body. These shall fit into the		
	pockets of the front and rear corner posts and lap over the	9	
	inside of the along their full bottom length attached to the	!	
	dump body with threaded fasteners. Welding is unaccepta	able.	
	All side boards equipped with inside D rings for installation	1	
	and removal.		
JJ.	24" X 36" rubber mud splash guards will be the no sail	YES	_NO
	Type and positioned behind each rear drive wheel. These	should	
	be mounted to the dump body in compliance with state ar	nd	
	local statues with regards to position and function.		
KK.	One 12" X 24" 10-gauge stainless steel flap welded	YES	_NO
	to body with a 24" X 20" rubbed flap bolted to it. This flap	should be	
	located in front of each drive wheel and fastened to the bo	ottom	
	of the dump body by welding.		
LL.	All steel painted surfaces shall be high pressure cleaned ar	nd <b>YES</b>	NO
	phosphate prior to application of enoxy primer		

MM.	All exterior body surfaces will be treated with a	YES	NO
	biodegradable cleaner.		
NN.	All normally painted areas and undersides must be	YES	NO
	undersides must be first thoroughly washed to remove oil,		
	welding debris and dirt before priming. These areas will		
00.	then be thoroughly primed prior to application of finish pa Underside and chassis area shall be gloss black industrial enamel.		NO
PP.	Dump body shall be primed then painted #6894	YES	NO
	blue single stage paint.		
QQ.	The entire body structure shall be constructed of new and unused material.	YES	NO
<u>HOIST</u>	<u>:</u>		
A.	Mailhot model CS-130-6-3 DA Class 100 Cylinder	YES	NO
	covered by a two-year manufacturer warranty.		
В.	Three (3) stage telescopic sealed bore with nitride	YES	NO
	sleeves.		
C.	Connecting pivots with replaceable greaseable	YES	NO
	bushings.		
D.	The cylinder should operate with the largest stage	YES	NO
	at the bottom. (Not inverted)		
E.	The one-piece modular cradle sub frame incorporates	YES	NO
	body props, body guides and greaseable bushings.		
F.	Cylinder collar shall permit 5° oscillation and	YES	NO
	be affixed to truck by mounting angles bolted		
	through sides truck frame.		

G.	6" X 6" X ½" structural steel rear hinge angle welded	YES	NO	_
	to the truck frame at this point. NO other welding shall			
	be done to the frame of the truck.			
Н.	2" 201 Stainless steel hinge pins connecting thru solid 2 ½	Z" YES	NO	_
	hinge blocks employing greaseable blocks.			
HYDR.	AULIC SYSTEM:			
A.	The hydraulic pump shall be an axial piston pressure	YES	NO	-
	and flow compensated load-sensing type.			
В.	The pump shall have a displacement of 5.61 cubic inches	YES	NO	_
	per revolution at maximum stroke which will deliver 23.7			
	GPM @ 1000 engine RPM.			
C.	The pump shall have a minimum of 2" inch suction line	YES	NO	-
	and ½" control drain line plumbed directly back to reserve	oir.		
D.	The pumps compensator shall have rear facing	YES	NO	_
	adjustments.			
E.	The pump shall be rated for 5800 PSI maximum and	YES	NO	-
	4800 PSI continuous.			
F.	The pump shall be <b>FORCE America TXV2</b> or prior approve	d YES	NO	-
	equal. An <b>OMFB series hot shift PTO</b> that is mounted to			
	the transmission shall drive the pump.			
SHUTI	DOWN SYSTEM			
G.	They system shall be designed so that when the float	YES	NO	_
	contacts close, the PTO will disengage and stop pump flow	W.		
Н.	In cab installation of PTO control switch and enunciator	YES	NO	_
	in control console will alert the driver that the PTO has			
	been disengaged.			

I.	The control console will also incorporate an override	YES	NO
	switch wired to de-energize the shutdown system to		
	facilitate diagnostics and equipment storage.		
HIGH P	PRESSURE FILTER		
J.	There shall be a high-pressure filter plumbed between	YES	NO
	the hydraulic pump and the control valve assembly.		
K.	The hydraulic filter shall be a 25-micron absolute and	YES	NO
	rated for 6000 psi.		
L.	The filter shall be model <b>HP17125VG30EPUG5S2AE7050P</b>	YES	NO
	or prior approved equal and be equipped with a visual and		
	electrical bypass indicator.		
<b>D.</b> 4		VEC	NO
IVI.	The electrical indicator shall be wired to the control	YES	_NO
	console.		

#### VT 35 RESERVOIR/VALVE ENCLOSURE

- YES\_\_\_\_NO\_\_\_
- The hydraulic reservoir will be of 35 gallons nominal capacity.
- The hydraulic reservoir will be constructed of 10-gauge 201 stainless steel with a 2 B finish and be internally baffled.
- The valve enclosure lid will protect from both road and pressure washer spray.
- For ease of removal by a single person, the valve enclosure lid shall weigh less than 22 lbs.
  - The valve enclosure lid shall be stainless steel.
- The valve enclosure lid shall be attached to the reservoir via (4) rubber straps that can be removed without the use of any tools.
- Mounting bracket is to be designed and supplied by the reservoir supplier.
- Mounting system should allow for a 1" frame clearance for frame obstructions.

- Shall be mounted in a manner as to not transmit any truck torsional loads thru the tank.
  - The enclosure will use a gasket-less passive technology.

(No rubber seals, gaskets, or weather stripping.)

- The enclosure lid will be removable within seconds by one person without the use of tools.
- All valve fittings, hose ends, filter, filler breather, sending units and any electrical connections are to be protected by enclosure cover.
- The reservoir supplier will provide all valve fittings (JJC connections) and pump the return line from the valve to the filter.
  - The use of bulkhead fittings is not permitted.
- The directional control valve must be easily accessible from all (6) sides without the use of tools.
- Hose exit and entrance must allow for components to be mounted adjacent to the enclosure.
- A 2" full flow brass ball valve shall be plumbed at the suction port of the tank.
  - A low oil/high temp sending unit shall be mounted in the reservoir.

The valve/tank assembly shall be a FORCE America model

"VT35G2-B-SP Valve/Tank Assembly"

|--|

FILTER			
A.	Hydraulic oil filter shall be mounted in the reservoir	YES	_NO
В.	Hydraulic filter shall be rated no less than 80 GPM.	YES	_NO
C.	Filter shall be ZINGA model TS-1600-25-1S0/25	YES	_NO
	<b>ZSRE-409-10E</b> micro-glass filter element and be equipped		
	with visual filter condition indicator gauge.		
HYDR/	AULIC CONTROL VALVE		
A.	Sectional 1 spool parallel circuit closed center control	YES	_NO
	valve. This section shall be four way for control of the		
	dump body hoist. Valve to have 500 lb. work port relief		

	on outside of truck frame on brackets adequate to support		
	valve and hosing.		
В.	The main control valve should be operated by level	YES	_NO
	Located on a riser to the immediate right of the driver seat	. The	
	lever shall be attached to the valve spool via flexible core		
	fully sealed control cables.		
C.	Single axis type dump body hoist control allows the raise/	YES	_NO
	lower function. The lower function shall be the position		
	toward the front of the truck. The dump body control will		
	be located nearest the driver. Lower function shall have a		
	push button lockout		
D.	The location of all controls must be placed in the truck cab	YES	_NO
	to allow convenient reach and operation by the driver whil	e	
	comfortably seated in an upright position.		
Ε.	All hydraulic lines and plumbing shall be of sufficient	YES	_NO
	capacity so as not to create heat or turbulence within		
	hydraulic system.		
F.	Suction line between reservoir and pump shall be a	YES	_NO
	minimum of 2 in. I.D. with a minimum SAE 100-R4 rating		
	and shall be secured on both ends via heavy duty banding		
	straps, radiator hose clamps unacceptable.		
G.	Protective covering to be applied where hose may	YES	_NO
	may contact abrasive edges.		
Н.	All pressure hoses, including signal sense to pump	YES	_NO
	shall have swivel fittings on both ends and have a minimum	า	
	SAE 100-R2 rating.		
l.	Return lines and case drain shall have minimum	YES	_NO
	SAE 100-R1 rating.		

built into control valve in A port. Valve shall be mounted

J.	Hydraulic lines shall be routed to minimize	YES	_NO
	interference with equipment and chassis components		
	requiring periodic servicing.		
K.	Support brackets, grommets, and tie wrap shall be	YES	_NO
	provided where appropriate to protect lines from damage		
	by abrasion, cutting or impact.		
L.	Hoses shall not be routed near exhaust manifolds, pipes,	YES	_NO
	bolts, sharp edges and exhaust system to prevent wear,		
	fatigue or fire. Pipe fittings are not acceptable in any		
	high-pressure line.		
М.	Maximum distance between support clamps on all	YES	_NO
	hydraulic lines shall be 24 in.		
N.	Rigid 304 Stainless Hydraulic tubing shall be used to	YES	_NO
	route hydraulics from the front to rear of the chassis		
	and body.		
Ο.	Hydraulic hose whips are allowed for pivot point	YES	_NO
	connections between tubing runs for final terminations at		
	valve bodies, drive motors.		
Ρ.	Tubing ends shall be flared ends with all stainless steel	YES	_NO
	nuts and hardware and shall accommodate tapered JIC		
	fittings.		
Q.	Tubing shall be fastened to the chassis with	YES	_NO
	polyethylene shock resistant pipe clamps to cross supports	i.	
R.	The valve body shall have a high-quality liquid filled direct	YES	_NO
	reading gauge, visible when the enclosure cover is remove	d	
	showing pressures when trouble shooting the system.		
	The gauge shall be permanently plumbed into the valve bo	dy	
	providing standby and full system pressure readings. High		
	pressure gauge must be 5.000 PSI gauge.		

<u>ELEC</u> 1	TRICAL:		
Α.	. LED clearance, marker and identification lights. All	YES	NO
	lights and reflectors must comply with Illinois Vehicle Co	ode	
	and F.V.V.S.S. #108 requirements as amended.		
Ce	ertification required.		
В.	Stainless bolts should be used for installation of cab	YES	NO
	roof lighting. The legs, cross bar and gussets must be		
	fabricated of 12-gauge 304 stainless steel and welded		
	together as an assembly. The legs should be bolted thr	ough	
	the cab roof side using # 12-24 stainless steel truss head	d	
	machine screws with nylon stop nuts. A minimum of for	ur (4)	
	bolts should be used on each side. The Cross bar should	d be	
	a maximum of 72" long and not extend past the cab wid	dth.	
	When installed, the roof bar should maintain the lowes	t profile	
	possible and clear the highest point of the cab by 2" ma	ximum.	
C.	To maintain the low profile of the roof bar,	YES	NO
	all air horns, radio antennas and similar features		
	must not be installed on the cab roof.		
D.	. Whelen LED System Model # DOT IL L2KD LED special	YES	NO
	warning lights which consist of:		
	(1) Whelen Justice Bar with 2 forward facing work light		
	heads. This light bar is mounted on a custom stainless		
	steel bar.		

Ε.	Four 500 Series directional amber LED heads measuring	YES	_NO
	5" X 1 5/8" are mounted in 10-gauge stainless steel		
	housings and recessed into the rear corner posts of the		
	dump body. These housings will also accommodate one		
	500 series brake/tail/turn LED signal light with a red lens.		
	These lights are located immediately below the amber		
	LED heads. All light heads located in the recessed stainless	5	
	steel housings are equipped with Deustch waterproof plug	S.	
	All LED heads are powered by an internal flasher located in	1	
	each light head. (3) switches located on the switch panel		
	will control the LED system.		
F.	2 LED work lights mounted on a light bar facing forward.	YES	_NO
G.	Right and left 700 series stop, turn, amber lights in	YES	_NO
	stainless steel housings mounted on the back of the dump		
	body cab shield. Facing rear ward.		
Н.	All wire entry points in the water proof terminal box shall	YES	_NO
	be compression type and shall tightly fit the wire jacket at		
	the entry point. The feeder cable shall terminate with a		
	standard 6 way round trailer connector plug and socket		
	located adjacent to the pintle hook.		
I.	PAR 46 LED sealed beam spreader light (minimum	YES	_NO
	1350 lumens) with a flood style pattern should be enclose	d	
	in a rubber housing. The light is attached to the lower side	<u> </u>	
	of the LED mounting platform located on the rear of the		
	material spreader hoper. The light should illuminate the		
	area covered by the discharge pattern of the material		
	spreader. The switch is located on the switch panel.		
J.	Two model 600 LED chassis mounted brake/tail/stop/turn	YES	_NO
	lights will replace the OEM units. Located at the rear end		
	of the frame rails in a water tight fabricated stainless steel		
	box providing protection from impact. A 600 LED lamp wit	:h	

clear lens will be provided and installed at or near the center of the rear chassis frame and serve as back up light. (2) LED lights, one on each side, should be recessed into the rear corner posts of the dump body and act as rear side marker lights.

K.	All wire entry points in the waterproof terminal box shall YESNO
	box shall be compression type and tightly fit the wire jacket
	at the entry point. The original equipment chassis wiring
	running to the tail lights shall not be cut, spliced or tampered
	within any way. If it becomes necessary to disconnect this
	wiring in order reroute, it must be disconnected inside the tail
	light terminal box and reconnected there upon completion.
	The wiring harness shall be used without cutting or splicing
	and shall terminate only in the two rear corner posts of the
	dump body and truck cab. Wiring for marker lights, clearance
	lights, backup alarms or other electrical accessories whether
	specified or not shall be connected in rear light waterproof
	box, surface mounted at the rear of the chassis frame and
	located on the rear face of the rear frame cross member to
	provide easy access for maintenance.
L.	All wiring shall be in continuous runs without splicing and YESNO
	color coding shall be consistent along the entire wire length.
	No connections should be made to the harness except in
	the cab of the truck. "Tap in" connectors such as Scotch locks
	are not permitted in this or any City of Joliet fleet vehicles.
	Use of such will result in non-compliance of specifications.
M.	Frame mounted Class C 97 db. Electronic back-up alarm YESNO

back-up light circuit of the truck chassis.

N.	Buell Strombo air horn mounted behind the front bumper	YES	NO
	on each frame rail. NO EXCEPTIONS DUE TO FLEET		
	STANDARDIZATION. Horns should be connected to operate	te	
	simultaneously and placed so sound projects forward thro	ugh	
	a hole in the bumper controlled by an electrically operated	d	
	air valve located near the horns. The air valve shall be		
	operated by the horn button on the steering wheel.		
0.	Cab installed electronic trailer brake controller with	YES	NO
	manual lever for braking without the use of truck brake		
	pedal. Shall have adjustable sensitivity increments (0-10)		
	controller must be compatible with factory wiring.		
PINTL	E HOOK:		
A.	The 30,000 lb. capacity hook should be mounted	YES	NO
	beneath the rear hinge of the dump body by a full		
	face ¾" plate welded to both the hinge angle bottom		
	and frame rail supports and extend downward to place		
	the hitch 26" from the ground. Adequate bracing		
	should ensure full capacity of the hitch. The provided		
	safety chain loops should be adjacent to the pintle hook.		
	A license plate bracket and light will be mounted above		
	the hitch.		
В.	(2) tow hooks should be mounted to the rear frame	YES	NO
C.	A seven-way flat pin with brake wiring. Female trailer	YES	NO
	light receptacle should be installed adjacent to the pintle		
	hook. The 14-gauge seven conductor wiring should be		
	continuous with each conductor being separately insulate	d.	
	The cord should terminate inside the recentacle at both th	ne	

<u>MI</u>	SCELLANEOUS:
Α.	When delivered, the vehicle shall comply with all applicable IDOT, EPA, OSHA and FMVSS regulations and all provisions of the Illinois Vehicle Code as they apply to vehicles of this division. Certification as to the compliance is required. A valid certificate of safety compliance issued by the Illinois Department of Transportation shall be affixed.

# ALL BIDDERS SHALL LIST THE FOLLOWING INFORMATION REGARDING THE TRUCK CHASIS AND BODY SUPPLIED

YEAR OF TRUCK	
MAKE OF TRUCK	
MODEL OF TRUCK	
MAKE/MODEL OF DUMP BODY	
GVWR	
WHEEL BASE	
C.A.	
ENGINE	
ALTERNATOR (IN AMPS)	
FRONT AXLE (IN LBS)	

FRONT SPRINGS	
REAR AXLE (IN LBS)	
REAR SPRINGS	
ENGINE (MANUFACTURER)	
ENGINE (RATINGS)	
FUEL TANK CAPACITY (IN	
GALLONS)	
TRANSMISSION	
FRONT TIRE & WHEELS	
(MANUFACTURER)	
FRONT TIRES & WHEELS (SIZE)	
REAR TIRES & WHEELS	
(MANUFACTURER)	
REAR TIRES & WHEELS (SIZE)	

# CITY OF JOLIET STATE OF ILLINOIS

## PROPOSAL FORM

NOTE: ALL BLANKS ON EACH AND EVERY SHEET OF THIS PROPOSAL SHALL BE COMPLETED. FAILURE TO COMPLETE ALL BLANKS SHALL BE GROUNDS FOR REJECTION OF BIDS. TO THE MAYOR AND CITY COUNCIL OF JOLIET, ILLINOIS: 1. PROPOSAL OF \_\_\_\_\_ (Name and Address of Bidder) TWO (2) HEAVY DUTY TANDEM AXLE CAB / CHASIS 6X4 TRUCKS WITH DUMP BODY AND ACCESSORIES, equiped in accordance with and as specified in these proposal documents. ONE EACH: \$ TOTAL AMOUNT FOR TWO (2) TRUCKS: \$ Anticipated Delivery Date: \_\_\_\_\_ Delivery of vehicle is to include price of delivery to City of Joliet Fleet Services, 402 N. Chicago St., Joliet, IL 60432 SUBMITTED BY: Print Name of Company Signature of person authorized to sign bid TITLE ADDRESS E-MAIL ADDRESS: \_\_\_\_\_\_\_\_\_

PHONE ( )

DATE

	<ol><li>This set of contract documents shall remain intact and shall be submitted in its entirety with the proposal.</li></ol>		
(IF AN II	NDIVIDUAL)		
	SIGNATURE OF BIDDER	(SEAL)	
	BUSINESS ADDRESS		
******	******************	*********	
(IF A CC	D-PARTNERSHIP)		
	FIRM NAME	(SEAL)	
	SIGNED BY	(SEAL)	
	BUSINESS ADDRESS		
Address Member	ames andses of Allses of the firm		
(IF A CC	ORPORATION)		
	CORPORATE NAME		
	SIGNED BYPresider	 nt	
	BUSINESS ADDRESS		
(CORPC	ORATE SEAL)		
	PRESIDENT		
Insert	SECRETARY		
Names of Officers			
ATTEST	Γ: Secretary	_	

# CONTRACT SPECIFICATION - DEVIATIONS AND SUBSTITUTIONS

Pursuant to Section 15 of the Instructions to Bidders, please list any and all deviations and substitutions made in the Contract Specifications here:

All deviations or substitutions must meet or exceed the specifications.

SUBMITTED BY:			
Print Name of Company			
BY:			
Signature of person authorized to sign bid			
TITLE			
ADDRESS			
E-MAIL ADDRESS:			
PHONE ()			
DATE			

# (NOTE: These affidavits must be completed by an authorized representative of the bidder)

# **AFFIDAVITS**

# Business Status of Bidder

BIDDER/APPLICANT:			
Name			
	Principal place of business		
Address			
	City, State, Zip Code		
	The Bidder is	s a:	
	Corporation		
	Partnership		
	G 1 D 1:		
	Other (please explain:		)
	(F. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1.		/
	Corporation		
The state of	of incorporation is:		
The registe	ered agent of the corporation in Illinois is:		
Name			
Address			
City, State, Z	Zip		
The office	ers of the corporation are:		
	President	Secretary	
	Vice President	Treasurer	

The Corporation is authorized to do business in the State of Illinois

# **Limited Liability Company**

Illinois is:  Illinois is:  inpany are:
Illinois is:
Illinois is:
Illinois is:
Name
Address
City, State
s
following assumed names:

## **BID RIGGING AND BID ROTATING**

## **Section 2:** That in connection with this solicitation for bids/proposals:

- A. The bid is not made in the interest of or on behalf of any undisclosed person, partnership, company, association, organization or corporation;
- B. The bidder has not in any manner directly or indirectly sought by consultation, communication or agreement with anyone to fix the bid price of said bidder or any other bidder or to fix any overhead profit or cost element of such bid price or that of any other bidder or to secure any advantage against the public body awarding the contract or anyone interested in the proper contract;
- C. The bid is genuine and not collusive or sham;
- D. The prices or breakdowns thereof and any and all contents which had been quoted in this bid have not been knowingly disclosed by the bidder and will not be knowingly disclosed by the bidder directly or indirectly to any other bidder or any competitor prior to opening;
- E. All statements contained in such bid are true;
- F. No attempt has been made or will be made by the bidder to induce any other person or firm to submit a false or sham bid;
- G. No attempt has been made or will be made by the bidder to induce any other person or firm to submit or not to submit a bid for the purpose of restricting competition;

#### Section 2a

## **NON-COLLUSION**

- A. No officer or employee of the City of Joliet has a direct or indirect pecuniary interest in this bid.
- B. No officer or employee of the City of Joliet has disclosed to the bidder any information related to the terms of a sealed bid.
- C. No officer or employee of the City of Joliet has informed the bidder that the bid will be accepted only if specified persons are included as subcontractors.
- D. Only the bidder will be entitled to the proceeds of the contract if this bid is accepted by the City of Joliet.
- E. This bid is made without the benefit of information obtained in violation of law.

### **Section 3.** The undersigned further states that: (circle A or B)

- A. He is the person in the bidder's organization responsible within that organization for the decision as to the prices being bid herein and that he has not participated, and will not participate, in any action contrary to paragraphs A through G above; or
- B. He is not the person in the bidder's organization responsible within that organization for the decision as to the prices being bid herein but that he has been authorized to act as agent for the persons responsible for such decision in certifying that such persons have not participated, and will not participate, in any action contrary to paragraphs A through G above and as their agent does hereby so certify; and
- C. That he has not participated, and will not participate, in any action contrary to paragraphs A through G above.
- **Section 4.** The undersigned certifies that the bidder has never been convicted for a violation of State laws prohibiting bid rigging or bid rotating.

# THE REQUIREMENTS OF THE ILLINOIS DRUG FREE WORKPLACE ACT

### **Section 5.** The undersigned will publish a statement:

- A. Notifying employees that the unlawful manufacture, distribution, dispensation, possession, or use of a controlled substance is prohibited in the aforementioned company's workplace;
- B. Specifying the actions that will be taken against employees for violations of this prohibition;
- C. Notifying the employees that, as a condition of their employment to do work under the contract with the City of Joliet, the employees will:
  - 1. Abide by the terms of the statement; and
  - 2. Notify the aforementioned company of any criminal drug statute conviction for a violation occurring the in the workplace not later than five (5) days after such a conviction.
- D. Establishing a drug free awareness program to inform the aforementioned company's employees about:

- 1. The dangers of drug abuse in the workplace;
- 2. The aforementioned company's policy of maintaining a drug free workplace;
- 3. Any available drug counseling, rehabilitation, and employee assistance programs; and
- 4. The penalties that may be imposed upon employees for drug violations.
- E. Making it a requirement to give a copy of the statement required by Section 5. to each employee engaged in the performance of the contract with the City of Joliet and to post the statement in a prominent place in the workplace;
- F. Notifying the City of Joliet within ten (10) days after receiving notice under Section 5.C.2. from an employee or otherwise receiving actual notice of such a conviction;
- G. Imposing a sanction on, or requiring the satisfactory participation in a drug abuse assistance or rehabilitation program by, any employee who is so convicted, as required by Section 6., below;
- H. Training personnel to effectively assist employees in selecting a proper course of action in the event drug counseling, treatment, and rehabilitation is required and indicating that an effectively trained counseling and referral team is in place;
- I. Making a good faith effort to continue to maintain a drug free workplace through implementing these requirements.
- J. Making a good faith effort to continue to maintain a drug free workplace through implementation of this policy.
- **Section 6.** The undersigned further affirms that within thirty (30) days after receiving notice from an employee of a conviction of a violation of the criminal drug statute occurring in the aforementioned company's workplace he shall:
  - A. Take appropriate personnel action against such employee up to and including termination; or
  - B. Require the employee to satisfactorily participate in a drug abuse assistance or rehabilitation program approved for such purposes by a federal, state, or local health, law enforcement, or other appropriate agency.

## TAX COMPLIANCE

**Section 7.** The undersigned on behalf of the entity making the foregoing proposal certifies that neither the undersigned nor the entity is barred from contracting with the City of Joliet because of any delinquency in the payment of any tax administered by the State of Illinois, Department of Revenue, unless the undersigned or the entity is contesting, in accordance with the procedures established by the appropriate revenue act, liability of the tax or the amount of tax.

**Section 8.** The undersigned or the entity making the proposal or bid understands that making a false statement regarding delinquency in taxes is a Class A Misdemeanor and in addition, voids the contract and allows the municipality to recover all amounts paid to the individual or entity under the contract in a civil action.

## NON DISCRIMINATION AND EQUAL EMPLOYMENT OPPORTUNITY

**Section 9.** This EQUAL EMPLOYMENT OPPORTUNITY CLAUSE is required by the Illinois Human Rights Act and the Rules and Regulations of the Illinois Department of Human Rights published at 44 Illinois Administrative Code Section 750, et seq..

**Section 10.** In the event of the contractor's noncompliance with any provision of this Equal Employment Opportunity Clause, the Illinois Human Right Act, or the Rules and Regulations for Public Contracts of the Department of Human Rights (hereinafter referred to as the Department) the contractor may be declared nonresponsible and therefore ineligible for future contracts or subcontracts with the State of Illinois or any of its political subdivisions or municipal corporations, and the contract may be canceled or avoided in whole or in part, and such other sanctions or penalties may be imposed or remedies involved as provided by statute or regulation.

During the performance of this contract, the contractor agrees:

- A. That it will not discriminate against any employee or applicant for employment because of race, color, religion, sex, national origin or ancestry; and further that it will examine all job classifications to determine if minority persons or women are underutilized and will take appropriate affirmative action to rectify any such underutilization.
- B. That, if it hires additional employees in order to perform this contract, or any portion hereof, it will determine the availability (in accordance with the Department's Rules and Regulations for Public Contracts) of minorities and women in the area(s) from which it may reasonably recruit and it will hire for each job classification for which employees are hired in such a way that minorities and women are not underutilized.
- C. That, in all solicitations or advertisements for employees placed by it or on its behalf, it will state that all applicants will be afforded equal opportunity without discrimination because of race, color, religion, sex, marital status, national origin or ancestry, age, physical or mental handicap unrelated to ability, or an unfavorable discharge from military service.

- D. That it will send to each labor organization or representative of workers with which it has or is bound by a collective bargaining or other agreement or understanding, a notice advising such labor organization or representative of the contractor's obligations under the Illinois Human Rights Act and the Department's Rules and Regulations for Public Contract. If any such labor organization or representative fails or refuses to cooperate with the contractor in its efforts to comply with such Act and Rules and Regulations, the contractor will promptly so notify the Department and the contracting agency will recruit employees from other sources when necessary to fulfill its obligations thereunder.
- E. That it will submit reports as required by the Department's Rules and Regulations for Public Contracts, furnish all relevant information as may from time to time be requested by the Department or the contracting agency, and in all respects comply with the Illinois Human Rights Act and the Department's Rules and Regulations for Public Contracts.
- F. That it will permit access to all relevant books, records, accounts and work sites by personnel of the contracting agency and the Department for purposes of investigation to ascertain compliance with the Illinois Human Rights Act and the Department's Rules and Regulations for Public Contracts.
- G. That it will include verbatim or by reference the provisions of this Equal Employment Opportunity Clause in every subcontract it awards under which any portion of the contract obligations are undertaken or assumed, so that such provisions will be binding upon such subcontractor. In the same manner as the other provisions of this contract, the contractor will be liable for compliance with applicable provisions of this clause by such subcontractors; and further it will promptly notify the contracting agency and the Department in the event any subcontractor fails or refuses to comply therewith. In addition, the contractor will not utilize any subcontractor declared by the Illinois Human Rights Department to be ineligible for contracts or subcontracts with the State of Illinois or any of its political subdivisions or municipal corporations.
- **Section 11.**For the purposes of subsection G of Section 10, "Subcontract" means any agreement, arrangement or understanding, written or otherwise, between a public contractor and any person under which any portion of the public contractor's obligations under one or more public contracts is performed, undertaken or assumed; the term "subcontract," however, shall not include any agreement, arrangement or understanding in which the parties stand in the relationship of an employer and an employee, or between a bank or other financial institution and its customers.
- **Section 12**. It is expressly understood that the foregoing statements and representations and promises are made as a condition to the right of the bidder to receive payment under any award made under the terms and provisions of this bid.
- **Section 13.** Have written sexual harassment policies that shall include, at a minimum, the following information: (i) the illegality of sexual harassment; (ii) the definition of sexual harassment under State law; (iii) a description of sexual harassment, utilizing examples; (iv) the vendor's internal complaint process including penalties; (v) the legal recourse, investigative and complaint process

available through the Department and the Commission; (vi) directions on how to contact the Department and Commission; and (vii) protection against retaliation as provided by Section 6-101 of this Act. A copy of the policies shall be provided to the Department upon request.

**Section 14.** In the event that this contract is subject to Executive Order 11246, Seller certifies that it (1) is in compliance with Section 202 thereof and the Rules and Regulations issued thereunder; (2) does not and will not provide or maintain at any of it's establishments, or permit it's employees to perform their services at any location under its control where there are maintained, segregated facilities, and (3) agrees that a breach of this Certification violates the Equal Employment clause of Executive Order 11246. "Segregated Facilities," means facilities which are in fact segregated on a basis of race, color, creed, sex, religion or national origin, because of habit, local custom, or otherwise.

# THE AMERICANS WITH DISABILITIES ACT

**Section 15.** As a condition of receiving this contract, the undersigned vendor certifies that services, programs and activities provided under this contract are and will continue to be in compliance with the Joliet Accessibility Code.

Signed by:		
	[name]	
	[title]	
Subscribed and Sworn to before me this	day of	, 20
By:		
,	Notary Public	

-seal-

# **AGREEMENT**

between the City of Joliet, an Illinois	to on the date stated below by and between the Municipal Corporation (hereinafter "City") and (hereinafter "Contractor").
Documents, the Contractor agrees to materials necessary for the proper comp	romises of the parties set forth in the Contract timely perform all work, furnish all labor and letion of the work; and the City agrees to pay for ments. The Contractor further agrees to comply ge Act (820 ILCS 130/1 et seq.).
The Contract Documents shall of hereby made part of this Agreement as it	consist of the following documents which are frecited at length herein:
6) Affidavits 7) Performance Bond and P 8) Addenda  IN WITNESS WHEREOF, the Ci	ngs istent with Contract Documents)
201 CITY OF JOLIET,	,,,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,,
An Illinois Municipal Corporation,	
	Print name of Contractor
By: Steve Jones Interim City Manager	By:
Attest:	Print Name:
Christa M. Desiderio City Clerk	Title:
Approved as to form:	
Martin J. Shanahan, Jr. Corporation Counsel	_